# TACOMA SLAG STUDY VOLUME 1

**FINAL REPORT** 

### Submitted to:

SAIC - TSC 18706 North Creek Parkway Suite 110 Bothell, Washington 98011

Submitted by:

Keystone/NEA 12242 S.W. Garden Place Tigard, Oregon 97223

May 20, 1991



### TACOMA SLAG STUDY

### FINAL REPORT

### Prepared for:

US EPA Region X
as a subcontract from
SAIC-TSC
18706 North Creek Parkway, Suite 110
Bothell, Washington 98011

Prepared by:

John E. Wade, John A. Cooper, and Charles R. Lytle

Keystone/NEA 12242 S.W. Garden Place Tigard, Oregon 97223

May 20, 1991

### TACOMA SLAG STUDY

Prepared by:

Keystone/NEA 12242 S.W. Garden Place Tigard, Oregon 97223

May 20, 1991

Approvals:

Prepared by:

John E. Wade

Manager, Ambient Air Monitoring

Projects

Project Director:

John A. Cooper, Ph.D. President

Director of Analytical Services:

Charles R. Lytle, Ph.D.

Vice President

### **ACKNOWLEDGEMENTS**

This report was prepared for the United States Environmental Protection Agency under a subcontract to SAIC (contract #16-91001582). We would like to acknowledge the substantial contributions of David Maughan, Senior Toxicologist and contract technical officer, for his advice, suggestions and constructive criticism. Dan Redline, John Moulton and Rick Hanna provided valuable help in the field work and preparation of the sampling and analysis plan. We would also like to acknowledge the contributions of Pam Bowes and Marilyn Stinnett, who typed the draft and final documents.

## TABLE OF CONTENTS

		<u>Page</u>
1.0	NTRODUCTION	1-1
2.0	BACKGROUND	2-1
	2.1 Discussion of the Problem	2-1
	2.2 Background on Arsenic and Lead	2-3
	2.3 Motivation for the Investigation	2-4
3.0	EXPERIMENTAL PROCEDURES	
	3.1 Overview	3-1
	3.2 Field Sampling Procedure	3-3
	3.3 Preparation of Samples for Laboratory Analyses	3-8
	3.4 Laboratory Analysis	3-9
	3.5 Data Quality Objectives	3-14
4.0	RESULTS AND DISCUSSION	4-1
	4.1 Particle Size Distribution	4-1
	4.2 X-Ray Fluorescence Analysis	
	4.3 CMB Analysis of XRF Results	4-9
	4.4 Floor and Refrigerator Wipes	4-10
	4.5 Analysis of Driveway Slag	4-12
	4.6 Analysis of Yard Soil	4-13
	4.7 Analysis of Vacuum Dust	4-15
	4.8 Analysis of Ground Slag Samples	4-15
	4.9 Method Validation and Quality Control	4-18
5.0	CONCLUSIONS AND RECOMMENDATIONS	5-1
6.0	BIBLIOGRAPHY AND REFERENCES	6-1
<u>AP</u>	ENDICES	
	APPENDIX A: LABORATORY ANALYSIS REPORT, QUAL REPORT, AND CALCULATION	ITY ASSURANCE
	APPENDIX B: CHEMICAL MASS BALANCE ANALYSIS R	ESULTS

### 1.0 INTRODUCTION

This report describes results of an investigation of concentrations of lead and arsenic in driveways and homes in the vicinity of the Tacoma smelter. Slag from the smelter has been used by homeowners in the area as a driveway surfacing and paving material. All of the homes selected for study were more than four miles from the smelter, which is no longer in operation.

The main objectives of this investigation were to:

- investigate the concentrations of lead and arsenic in residential driveways surfaced with slag
- determine the concentration of lead and arsenic in the yards of these residences
- test the levels of arsenic and lead in dust inside the selected dwellings
- compare the chemical signature of these elements found in the driveways to those found in the associated dwellings
- examine the concentration of lead and arsenic in slag, house dust and soils as a function of particle size.

This report is organized in six sections. This section defines the purpose of the report, study objectives and report organization. Section 2 provides background for the investigation and localities of the sample sites. Section 3 provides a description of the experiment and includes field sampling and laboratory procedures, as well as quality assurance methods used. Section 4 presents results from the laboratory analysis of samples and data collected in the field. Section 5 presents conclusions and recommendations for the study. A bibliography and references are presented in Section 6.

The report also has three appendices. Appendix A is a summary of the laboratory analysis report. Appendix B presents the Chemical Mass Balance Analyses. Appendix C is the Chain of Custody Record for field sampling.

Two separate volumes accompany the report. Volume 2, Sampling and Analysis Plan, provides a detailed discussion of the quality assurance plan, field standard operating procedures and laboratory standard operating procedures. Volume 3 includes miscellaneous documentation, including photocopy of the field notebook and a log of photographs taken during sampling.

### 2.0 BACKGROUND

Arsenic and lead, two elements associated with adverse health effects, have been identified in significant concentrations in slag deposited around a former primary copper smelter near Ruston, Washington. The smelter operated between 1890 and 1985. The former facility is within an area defined by the United States Environmental Protection Agency (EPA) as the Commencement Bay Nearshore Tideflats Superfund site and is listed on the CERCLA national priorities list. Slag from the smelter has been used by homeowners for paving and surfacing (e.g. in driveways) and for ornamental purposes.

The objective of this study was to measure the concentrations of arsenic and lead in slag deposited in driveways of homes in the Ruston-Tacoma-Gig Harbor area and to determine if these contaminants have migrated from the slag to yard soil and housedust. Contaminated soil and dust may be tracked into the home where it can settle on surfaces or objects that are contacted by people. People can also be exposed to contaminants in slag, soil and dust by breathing particles that have been released into the air by movements such as driving over a slag or dirt driveway, dusting, or digging into soil or slag. A person may ingest contaminants if hands that have come into contact with contaminated material are paced near or in the mouth. Similarly, soil may be ingested if dirty hands are used to touch food, gum, or cigarettes that are then placed into the mouth. This is of special concern for young children who often place their hands, toys and other objects into their mouths.

A typical chemical fingerprint of slag is presented in Figure 2.1. Arsenic and lead were identified as constituents of concern in slag. Both elements are naturally occurring constituents in the earth's crust, but can be toxic to plants and animals.

In this study, the concentrations of lead nd arsenic were determined in slag, soil, and housedust samples at three locations where slag was used as a driveway surface material.




Figure 2.1 ASARCO Ruston Slag Dump Composite Material > 38 Microns

These three locations, identified as Houses 1, 2 and 3, were sampled in an area near the former Tacoma Smelter on the 27th and 28th of November, 1990 (see Figure 2.2).

An additional sampling trip was made on the 14th of December, 1990, to re-collect driveway slag at Houses 2 and 3 because samples had been inadvertently mixed in the laboratory.

Sites selected for this study were chosen because they were more than four miles from the smelter. This would have eliminated substantial airborne deposition from ASARCO stack and fugitive emissions. The sites are all generally upwind of the former smelter's location on Commencement Bay in Puget Sound. The prevailing wind direction in the area is south-southwesterly; during the summer, northeast winds become another important flow regime. Figure 2.3 shows a more detailed map of the study area. Figure 2.4 is a five-year wind rose for the area around the former smelter.




Figure 2.2 Location of sampling sites.





Figure 2.3 Detailed map of the study area.



HOUR AVERAGE SURFACE WINDS

# PERCENTAGE FREQUENCY OF OCCURRENCE




Figure 2.4 A five-year wind rose for the area near the former smelter.

### 3.0 EXPERIMENTAL PROCEDURES

#### 3.1 Overview

The procedures in this section are described in greater detail in Volume 2, "Quality Assurance Plan for the Tacoma Slag Study." This section will summarize the field sampling and laboratory analysis procedures, and will discuss the techniques used to assess the precision, accuracy, completeness and representativeness of the results. Volume 3 accompanies this report and provides field notes and photographs taken during the field work.

The residences were selected by the EPA, with the primary selection criteria being sites located more than four miles upwind of the former smelter and inhabited by a cooperative homeowner. The field sampling was conducted in three different exposure media at three residences. Figure 3.1 shows a generalized diagram of the typical locations sampled at each house. The exposure media included: the <u>driveway</u>, where slag had been used as a surface paving material; the <u>yard</u>, where slag could be tracked on, leached into, and deposited from aerosolized dust; and the <u>house</u>, where soils, dust and slag could be tracked in and the dust redistributed from aerosolized dust particles.

In this investigation, dust samples from all three exposure media were divided into various size fractions prior to laboratory analysis of chemical constituents in the sample. This was done to determine if arsenic and lead concentrations increased as the size of the particle decreased. This is important because smaller particles are the ones that can be inhaled into the lungs and that adhere to the hands.

Laboratory analysis was used primarily to determine the lead and arsenic concentration as a function of particle size. The primary laboratory analysis procedures used were graphite furnace atomic absorption (GFAA) and inductively coupled plasma spectroscopy (ICP). ICP was used to screen for lower concentrations and to detect higher concentrations. If the measured concentration was less than five times the ICP instrument




Figure 3.1 Typical Locations Where Samples Were Collected in the Tacoma Slag Study (see X inside circle).

detection limit, the sample was reanalyzed using GFAA, which is capable of detecting lower concentration levels.

Some slag samples were mechanically ground in the laboratory to determine if a difference in concentration would occur when particles were ground to a finer size fraction. The coarsest fraction (78 to 150 microns) was ground to fine powder less than 38 microns in diameter and reanalyzed to determine the effect on arsenic and lead concentrations. Additionally, chemical analysis using X-ray fluorescence was used for selected samples to compare chemical fingerprints of the residential samples to chemical fingerprints of industrial slag deposited on the driveway.

### 3.2 Field Sampling Procedure

### 3.2.1 Driveway

At each residence, slag was collected from the driveway. The procedure for sampling slag in driveways is also described in Appendix A of Volume 2, Quality Assurance Plan. Two 5-gallon acid-washed buckets were used to collect slag samples from each location. The driveway slag material closest to the surface consisted primarily of large chunks of greater than 1/4 inch in diameter. Beneath the larger chunks were smaller chunks and fine sandy and silty material. Two bulk slag samples were composited and placed in a bucket. A total of four slag plots were collected per driveway.

The depth and distribution of slag over the driveway varied with each house. The sample site selection procedure was aimed at collecting samples in high traffic areas with slag depths representative of the driveway. An area of about 2x3 feet was raked to remove large pieces of slag. Stainless steel trowels were used to scoop up the slag and place it in the bucket. The boundary layer between the slag and underlying native soil was identified by a change in the color and texture of the soil and gravel. Large particles (>1/2 inch mesh screen) were presieved using a clean piece of screen. Each bucket contained about 30 pounds of slag material after sample collection.

The buckets were sealed after sample collection with an airtight lid, and chain of custody labels were placed on each container. Equipment was washed between residential sites, and the final rinse was collected as a field blank. One bucket, taken to the Tacoma and Gig Harbor areas, was not used for sample collection, but was afterwards treated as a trip blank.

### 3.2.2 Yard Sampling

Four locations in the yards of each residence were sampled. The locations represented four different exposure media. These locations were:

- the most likely slag containination area in the driveway where slag material would be tracked or leached onto the yard [Case A];
- on a diagonal line from the driveway to teh house entrance, no more than two feet from the driveway [Case B];
- on a diagonal line perpendicular to the end or side of the driveway and no less than 18 feet from the driveway [Case C]; and
- a sheltered location on the opposite side of or though the house from the driveway [Case D];

A 40x40 inch template was laid on the ground, and soil cones were taken from each corner of the template and composited in a bag. The soil sample contained the top inch of sod or soil. The soil corer was 2.5 cm in diameter and about six inches long. After each exposure media was sampled, the soil corer was rinsed. The final rinse after completing the yard soil sampling at a residence was collected as a field blank. One duplicate sample for each medium at each house was taken to test the representativeness of the sampling procedure and the precision of chemical analyses. During the sampling, new surgical gloves were worn at each location.

### 3.2.3 House Sampling

Inside the house three different locations were sampled:

• Top of the refrigerator or freezer

- Kitchen floors
- Front room carpets.

Dusts on top of a refrigerator represent a historical deposition of dusts at a breathing zone of most adults. Aerosolized oil and fumes from cooking often deposit on the refrigerator top and act as a surface coating which traps airborne dust. Kitchen floors are usually not carpeted and represent current dusts as a result of a large amount of indoor foot traffic. However, they are often one of the cleanest floor surfaces in a home. The living room carpet is a location upon which small children play, crawl and lay. Carpets may appear clean, but inefficient household vacuums may leave a considerable amount of dusts, soil, skin, hair fragments, food, and microorganisms in the carpet.

The kitchen floor and refrigerator or freezer top were sampled by wiping the surface with a low metal, alcohol-dampened cellulose swab. A 10x10 inch area on the top of the refrigerator or freezer and a 20x20 inch area on the floor were selected as representative sample areas. Surgical gloves were used during sampling and changed after each sample. One duplicate sample was taken on each surface to check the representativeness of the sample site selection, and a field blank was collected by opening a swab but not performing the wipe. A laboratory blank consisted of digestion of an unused wipe.

Carpet dust was sampled using two collectors. The first was the homeowner's household vacuum cleaner, and the second was an EPA specially designed household vacuum (HVS3 = High Volume Small Surface Sampler). The design and operation of the HVS3 has been described by Roberts et al. (1991), and in Volume 2. Figure 3.2 shows an illustration of the EPA HVS3 sampler. An area 18x54 inches was sampled unless the carpet was a throw rug or entry carpet. The amount of dust collected determined how many 18x54 plots were vacuumed. The carpet in House 1 was a short plush carpet. Less than two grams was collected at four 18x54 locations. At the second residence, with a level loop carpet, nearly 35 grams were collected in four locations. House




Figure 3.2 HVS3 Sampler.

3 had a very short plush carpet, and less than two grams of dust was collected in three sample locations. In House 3, a sculptured rug in an entryway yielded 8.8 grams from three 18x54 inch sample areas.

The HVS3 was cleaned between samples by running it for at least 20 seconds with intake nozzle off the carpet. Between households, the HVS3 was completely disassembled and cleaned with a 50% acetone and 50% pentane solution. The rinse was collected in a I-Chem bottle and labeled for laboratory analysis.

Samples were also collected from the household vacuum cleaner. At House 1, surgical gloves were used to remove a large handful of carpet debris and dust. At Houses 2 and 3, the entire contents of the disposable vacuum bags were collected. All three homes used upright vacuum cleaners.

### 3.3 Preparation of Samples for Laboratory Analyses

The driveway slag, yard soil, and dust collected from the household and EPA vacuum were dried and sieved, using a Tyler Sieve Shaker Model RX-24, into four size fractions (see Table 3.1). The sieving procedure is described in Volume 2, the Quality Assurance Plan. Prior to sieving and drying, samples were screened to remove particles and debris greater than 1/4 inch in diameter. Sample drying was done in the Blue-M Laboratory oven at 55°C until the sample no longer was losing weight with each reweighing of sample weight. The sample drying procedure is described in the SOP#026 Volume 2, Quality Assurance Plan.

As above, two 5-gallon buckets of driveway slag were collected at each residence. The two buckets were composited into one sample for each household prior to sieving the driveway slag. A coning and quartering compositing procedure is described in SOP#027 of Volume 2.

Table 3.1 SIZE FRACTIONS ANALYZED FOR CHEMICAL COMPOSITION IN THE TACOMA SLAG CHARACTERIZATION INVESTIGATION

Size Fraction	Tyler Screen Mesh Sieve	Particle Diameter (µm)
Fine (silts)	>400	< 38
Fine (sand)	400 < to 200	38 < to 75
Coarse (sand)	200 < to 80	75 < to 180
Very Coarse (fine gravel)	80 < to 18	180 < 1000

After compositing, each size fraction was weighed and relabeled. A 5 gram aliquot from each size fraction was removed from driveway and EPA vacuum collected dust samples. This 5 gram aliquot from each location was placed in sealed glass lab bottles, and sent to SAIC-TSC for further archiving. Additional aliquots were removed for grinding.

Grinding of driveway slag samples was accomplished with a ceramic mortar and pestle. Sample was ground until at least 1 gram passed through a 400 mesh Tyler Sieve. We found that slag dusts collected in the size fraction less than 180 microns were extremely difficult to grind. The dust became glassy and merely slid around. However, the size fraction greater than 180 microns could be ground for collection of some fine material. Ground sample were collected in I-Chem bottles and labeled for laboratory analysis.

Material collected in the Tyler pan below the 400 mesh sieve was weighed. If several grams were available after the SAIC 5 gram aliquot and 1 gram for ICP and GFAA analysis were extracted, then the remaining sample was aerosolized using a procedure described in Volume 2. Fine particles were resuspended onto 47mm Teflon filters using a Sierra Model 244 dichotomous sampler and special platforms, chambers and flow regulators (see Figure 3.3). The purpose of this resuspension was to obtain a thin film of slag and dust that could be analyzed by x-ray fluorescence.




Figure 3.3 Resuspension Apparatus

### 3.4 Laboratory Analysis

# 3.4.1 Acid Digestion of Household Wipes, House Dust, Yard Soil, and Driveway Slag

EPA Method 3050 was used for the acid digestion of samples collected in this study. This procedure was used to prepare sediments and soil samples for analysis by graphite furnace atomic absorption (GFAA) or inductively coupled argon plasma spectroscopy (ICP). This method is appropriate for both arsenic and lead.

The method requires a 1 to 2 gram sample. The sample is digested in nitric acid and hydrogen peroxide. The digestate is then refluxed with either nitric acid or hydrochloric acid. Dilute hydrochloric acid is used as the final reflux acid. Preparation blanks are carried throughout the entire sample preparation and analytical process. Duplicate samples are processed at a 20% rate and spiked samples are employed to determine accuracy. Four outside calibration standards were provided by SAIC-TSC as a quality control check.

### 3.4.2 Arsenic and Lead Using ICP and GFAA

Soil samples digested using EPA Method 3050 were then analyzed by inductively-coupled plasma emission spectroscopy (ICP, EPA Method 6010) or graphite furnace atomic absorption spectroscopy (GFAA, EPA Methods 7060 and 7421).

Samples for ICP were analyzed on a Perkin-Elmer Model 40 sequential spectrometer using the instrumental and data workup guidelines stated in the EPA protocols. ICP Instrument detection limits for arsenic and lead were both 0.1 ppm. Samples with concentrations less than 0.5 ppm were reanalyzed by GFAA. GFAA analyses were done on a Perkin-Elmer Model 5000Z spectrometer equipped with Zeeman background correction and electrodeless discharge lamps. Instrumental conditions and data workup followed the guidelines given in the protocols described in the Quality Assurance

Plan for each analysis. Detection limits in the digestate were 0.001 ppm for arsenic and 0.002 ppm for lead using GFAA.

### 3.4.3 Elemental Analysis Using XRF

X-ray fluorescence (XRF) was used to compare the elemental composition of house dust to driveway slag. Fine material passing through the 400 mesh Tyler Sieve was aerosolized on a filter and analyzed by XRF. X-ray fluorescence as configured at Keystone/NEA is only appropriate for analysis of aerosols deposited on membrane-type filters. The procedure is described in Volume 2, SOP#010, using Protocol 4 (see Table 3.2).

### 3.5 Data Quality Objectives

### 3.5.1 Quality Assurance Objectives

The primary objective of the project QA program is to ensure that all data collected and prepared by Keystone/NEA are of known and of acceptable quality. The quality of data is known when all components are thoroughly documented and results for quality control samples fall within prescribed limits. The data must be verifiable and defensible under the scrutiny of litigation. Documented quality is the foundation of Keystone/NEA's services and provides clients with the confidence required to make difficult decisions and to take appropriate actions.

Quality assurance objectives for environmental analysis are defined in terms of the following characteristics:

- precision
- accuracy
- comparability
- representativeness
- completeness.

Table 3.2 TWO SIGMA INTERFERENCE FREE DETECTION LIMITS FOR X-RAY FLUORESCENCE ANALYSIS (ng/cm²) USING PROTOCOL 4.

Na	100	Ge	1.5
Mg	17	As	1.7
Αĺ	15	Se	1.8
Si	11	Br	2.1
P	4.4	Rb	2.5
S	16.3	Sr	3.0
Cl	8.8	Y	3.5
K	3.9	Zr	16
Ca	2.8	Мо	12
Sc	2.0	Pd	10
Ti	1.7	Ru	12
V	1.3	Ag	14
Cr	1.6	Cd	19
Mn	1.8	In	22
Fe	2.7	Sn	25
Co	1.6	Sb	28
Ni	1.5	Ba	112
Cu	1.4	La	120
Zn	1.4	Hg	3.4
Ga	1.4	Pb	5.3
		Th	7
		U	7

These characteristics are defined below and summarized in Table 3.3. Section 4.9.2 describes the results of our Quality Assurance and the degree to which the objectives described in this section were met.

### **Precision**

Precision is a measure of mutual agreement among repetitive measurements of the same property. Precision is calculated based on duplicate analysis. The relative percent difference (RPD) is given by:

[(Result 1 - Result 2)/Mean] x 100

### Accuracy

Accuracy is the agreement of a measurement (or an average of measurements), X, with an accepted reference, or true value, T. It is alternatively termed percent bias. Accuracy will be expressed as the percent recovery of the true value [100 \* (X/T)]. For spiked samples, percent recovery is calculated as follows:

Sample
Spike Recovery as % = plus Spike - Unspiked Sample x 100.
Spike Added

### Comparability

Comparability is defined as the confidence with which one data set can be compared to another. Comparability will be evaluated when possible on the basis of interlaboratory comparisons. In order to ensure data comparability, standard analytical procedures were used, with data reported in generally accepted units of measurement. Keystone/NEA currently conducts routine interlaboratory comparison studies on the analysis of air particulates by XRF.

### Representativeness

Representativeness can be defined both qualitatively and quantitatively and is dependent upon the selection of sample site and choice of sampling methods. The desired degree of representativeness is critical in planning for the collection of samples and the

Table 3.3
QUALITY OBJECTIVES FOR MEASUREMENT DATA

METHOD	MATRIX	ANALYTE	UNITS	DET. LIMIT <sup>a</sup>	ACCURACY TARGET	PRECISION TARGET <sup>b</sup>	COMPLETENESS TARGET
Gravimetry	Sieved Dust Air Filter	Mass Mass	mg mg	± 0.1 ± 0.001	± 5% ± 5%	± 5% ± 5%	99% 99%
Plasma Emission Spectroscopy	Sieved Dust	Arsenic Lead	mg/kg mg/kg	2.5	± 20%* ± 20%*		99% 99%
Graphite Furnace Atomic Absorption Spectroscopy	Sieved Dust	Arsenic Lead	mg/kg mg/kg	0.2	± 20%* ± 20%*		99% 99%
X-Ray Fluorescence 3 1 1	Sieved Dust Air Filters'	Aluminum Silicon Phosphorus Sulfur	ng/cm <sup>2</sup> ng/cm <sup>2</sup> ng/cm <sup>2</sup> ng/cm <sup>2</sup>	15 11 4.4 16.3	± 5% ± 5% ± 5% ± 5%	± 5% ± 5% ± 5% ± 5%	99% 99% 99% 99%
4		Chlorine Potassium Calcium Scandium	ng/cm <sup>2</sup> ng/cm <sup>2</sup> ng/cm <sup>2</sup> ng/cm <sup>2</sup>	8.8 3.9 2.8 2.0	± 5% ± 5% ± 5% ± 5%	± 5% ± 5% ± 5% ± 5%	99% 99% 99% 99%
		Titanium Vanadium Chromium Manganese	ng/cm <sup>2</sup> ng/cm <sup>2</sup> ng/cm <sup>2</sup>	1.7 1.3 1.6 1.8	± 5% ± 5% ± 5% ± 5%	± 5% ± 5% ± 5% ± 5%	99% 99% 99% 99%
		Iron Cobalt Nickel Copper	ng/cm <sup>2</sup> ng/cm <sup>2</sup> ng/cm <sup>2</sup>	2.7 1.6 1.5 1.4	± 5% ± 5% ± 5%	± 5% ± 5% ± 5% ± 5%	99% 99% 99% 99%
		Zinc Gallium Germanium Arsenic Selenium Bromine	ng/cm <sup>2</sup> ng/cm <sup>2</sup> ng/cm <sup>2</sup> ng/cm <sup>2</sup> ng/cm <sup>2</sup>	1.4 1.5 1.7 1.8 2.1	± 5% ± 5% ± 5% ± 5% ± 5%	± 5% ± 5% ± 5% ± 5% ± 5%	99% 99% 99% 99% 99%

### QUALITY OBJECTIVES FOR MEASUREMENT DATA

METHOD	HOD MATRIX ANALYTE UNITS		UNITS	DET. LIMITa		ACCURACY TARGET		SION ET <sup>b</sup>	COMPLETENESS TARGET	
		Rubidium	ng/cm <sup>2</sup>	2.5	±	5%	±	5%	99%	
		Strontium	ng/cm <sup>2</sup>	3.0	±	5%	±	5%	99%	
		Ytrinium	ng/cm <sup>2</sup>	3.5	±	5%	<u>±</u>	5%	99%	
		Zirconium	ng/cm <sup>2</sup>	16	±	5%	土	5%	99%	
		Molybdenum	ng/cm <sup>2</sup>	12	±	5%	<u>±</u>	5%	99%	
		Palladium	ng/cm <sup>2</sup>	10	±	5%	±	5%	99%	
		Silver	ng/cm <sup>2</sup>	14	±·	5%	±	5%	99%	
		Cadmium	ng/cm <sup>2</sup>	19	<u>±</u>	5%	<u>+</u>	5%	99%	
		Indium	ng/cm <sup>2</sup>	22	<u>±</u>	5%	<u> </u>	5%	99%	
•		Tin	ng/cm <sup>2</sup>	25	<u>±</u> '	5%	<u> </u>	5%	99%	
		Antimony	ng/cm <sup>2</sup>	28	± '	5%	±	5%	99%	
ω		Barium	ng/cm <sup>2</sup>	112	±	5%	±	5%	99%	
<u></u>		Lanthanum	ng/cm <sup>2</sup>	120	±	5%	±	5%	99%	
· ·		Mercury	ng/cm²	3.4	<u>±</u>	5%	±	5%	99%	
•		Lead	ng/cm <sup>2</sup>	5.3	± ±	5%	±	5%	99%	

<sup>\*</sup> Based on spike recovery.

Based on spike recovery.

For ICP, assumes 1.0 g digested in 100 mL.

For GFAA, assumes 1.0 g digested in 100mL.

For XRF, assumes analysis Protocol 4.

Expressed as relative percent difference when concentrations measure at least five times above instrumental detection limit.

subsequent uses of the data. Sample were collected to ensure they were representative of the component characteristics, to the greatest degree.

### Completeness

Completeness is the amount of valid data actually obtained compared to the amount that was expected to be obtained under anticipated sampling/analytical conditions. If incoming data represent less than the percentage expected, sampling and handling procedures will be reviewed and appropriate steps will be taken to increase completeness. The Keystone/NEA completeness target for laboratory data is 99 percent.

### 4.0 RESULTS AND DISCUSSION

Table 4.1 lists all the samples collected for laboratory analysis. The following subsections include the various laboratory analyses and quality control results, as well as chemical mass balance (CMB) apportionment results.

### 4.1 Particle Size Distribution

Table 4.2 presents the mass in each size fraction of all the samples that were sieved. Total masses in this table represent only those analyzed. The material with a diameter larger than 1/4 inch was screened and removed from the total sample. The percent mass by size fraction also indicates that most of the mass is in the large size fractions in the driveway, while in the house the mass of particles is more evenly distributed between size fractions (see Figure 4.1). The most variability in the largest size fraction (> 180  $\mu$ m) was in the EPA vacuum samples. In contrast, the least variation in the largest size fraction was in the household vacuum cleaner. In the smallest size fraction (< 38  $\mu$ m), the driveway slag had the smallest variation between different locations. Samples TS1127930 and TS1127931 were duplicates and show excellent agreement in terms of size distribution.

### 4.2 X-Ray Fluorescence Analysis

XRF analysis was performed on four house dust samples. The purpose of this analysis was to provide a chemical signature of the slag and dust that could be used in the chemical mass balance (CMB) investigation described in this section. The only house where there was sufficient dust in the HVS3 vacuum catch to perform XRF analysis was at House 2 in Gig Harbor. The catch in the smallest size fraction ( $< 38 \mu m$ ) household vacuum samples at Houses 2 and 3 were also sufficient to aerosolize for XRF analysis. Fine particulate ( $< 38 \mu m$ ) in the driveway slag were also aerosolized and analyzed by XRF. The results are shown in Figures 4.2 through 4.7.

#### Table 4.1

### FIELD SAMPLES AND QUALITY ASSURANCE SAMPLES FOR TACOMA SLAG STUDY

HOUSE 1
Id# Sample Description
TS1127901 Refrig wipe
TS1127902 Floor wipe
TS1127903 Carpet Grab
TS1127904 HVS3
TS1127905 Vacuum rinse
TS1127906 Driveway slag
TS1127907 Driveway slag
TS1127907 Brivewdy Slag TS1127908 Yard soil A
TS1127900 Yard soil B
TS1127910 Yard soil C
TS1127911 Yard soil D
TS1127912 Soil core rinse
HOUSE 2
TS1127913 Yard soil A
TS1127914 Yard soil B
15112/91/ Yald Soll C
TS1127918 Yard soil D
TS1127915 Driveway slag
TS1127916 Driveway slag
TS1127919 Spatula Rinse
TS1127920 Soil core Rinse
TS1127921 Refrig wipe
TS1127922 Floor wipe #1
TS1127923 Floor wipe
TS1127924 Floor wipe dup
TS1127925 Vacuum grab
TS1127926 Carpet HVS3
TS1127927 Entry HVS3
TS1127928 HVS3 rinse
TS1127929 Entry HVS3 rinse
HOUSE 3
TS1127930 Yard soil A
TS1127931 Yard soil A Dup
TS1127932 Yard soil B
TS1127932 Yard soil C
TS1127933 faid soil C
TS1127935 Driveway slag1
TS1127936 Driveway slag2
TS1127937 Wash core
TS1127938 Wash spatula
TS1127939 Vacuum Grab
TS1127940 Floor Wipe
TS1127941 Entry HVS3
TS1127942 Freezer wipe
TS1127943 HVS3 Fam rug
TS1127944 Freezer wipe Dup
TS1127945 Trip wipe blank
TS1127946 Entry Rinse HVS3
TS1127947 Fam Rug Rinse HVS3
TS1127948 Garage HVS3
TS1127949 Garage Rinse of HVS3

RESAMPLE HOUSE 2 & 3
TS1127950 Driveway slag House 2
TS1127951 Driveway slag House 2
TS1127952 Rinse
TS1127953 Driveway slag House 3
TS1127954 Driveway slag House 3
TS1127955 Trip Blank

QUALITY ASSURANCE SAMPLES TS1127956 Standard #1 CBS CCN-1 TS1127957 Standard #2 CBS SO-2 TS1127901 Standard #3 NBS 1648 TS1127902 Standard #4 CBS PO-1


NOTE: Yard soil samples A, B, C, and D refer to definitions in Section 3.2.2.

Table 4.2

PARTICLE SIZE DISTRIBUTION IN MICRONS

	•		Mass (g	rams)				Per	cent		
HOUSE #	SAMPLE ID#	SAMPLE LOC	>180	>75	>38	<38	Total	>180	>75	>38	<38
							<b></b>	~~ .~	40.70	0.47	7.40
1		DRIJVEWAY	427.5	111.2	49.6	18.8	607.1	70.42	18.32	8.17	3.10
2	TS1127950	DRIVEWAY	320	74.8	41	37.7	473.5	67.58	15.80	8.66	7.96
3	TS1127953	DRIVEWAY	184.3	100.6	42.2	13.4	340.5	54.13	29.54	12.39	3.94
		MEAN	310.60	95.53	44.27	23.30	473.70	64.04	21.22	9.74	5.00
•		STD	99.51	15.29	3.80	10.42	108.84	7.11	5.98	1.89	2.12
		STD ERROR	57.45	8.83	2.20	6.01	62.84	4.10	3.45	1.09	1.23
1	TS1127903	HVS3	.7	.3	.4	.05	1.45	48.28	20.69	27.59	3.45
2	TS1127926	HVS3	1.2	3.4	12.9	11.7	29.20	4.11	11.64	44.18	40.07
2	TS1127927	HVS3	.5	.1	1.9	2.6	5.10	9.80	1.96	37.25	50.98
3	TS1127941	HVS3	2.9	.13	3.4	1.2	7.63	38.01	1.70	44.56	15.73
3	TS1127943	HVS3	.4	.05	.45	. 15	1.05	38.10	4.76	42.86	14.29
3	TS1127948	HVS3	2.1	.05	.6	.1	2.85	73.68	1.75	21.05	3.51
•	, , , , , , , ,	MEAN	1.30	.67	3.28	2.63	7.88	35.33	7.09	36.25	21.34
		STD	.91	1.22	4.43	4.15	9.79	23.38	7.01	8.97	18.02
		STD ERROR	.37	.50	1.81	1.70	4.00	9.54	2.86	3.66	7.36
		SID LKKOK	.51	•	1.01		4.00	/		3.00	
1	TS1127904	VACUUM	15.7	7.5	4.1	0	27,30	57.51	27.47	15.02	.00
2 ·	TS1127925	VACUUM	141.75	60.8	61.2	23.5	287,25	49.35	21.17	21.31	8.18
3	TS1127939	VACUUM	57.4	26.8	26.8	4.5	115.50	49.70	23.20	23.20	3.90
		MEAN	71.62	31.70	30.70	9.33	143.35	52.18	23.95	19.84	4.03
		STD	52.43	22.03	23.47	10.18	.107,94	3.77	2.63	3.50	3.34
•		STD ERROR	30.27	12.72	13.55	5.88		2.18	1.52	2.02	1.93
•	TS1127908	YARD	0 4	5.5	2.5	.7	16.8	48.21	32.74	14.88	4.17
1			8.1								6.07
1	TS1127909	YARD	15	5.8	2.4	1.5	24.70	60.73	23.48	9.72	
1	TS1127910	YARD	19.2	10.9	4.2	4.4	38.70	49.61	28.17	10.85	11.37
1	TS1127911	YARD	6.8	.2	5.8	1	13.80	49.28	1.45	42.03	7.25
2	TS1127913	YARD	19.9	5.4	3.8	1.3	30.40	65.46	17.76	12.50	4.28
2	TS1127914	YARD	18.1	4	-4	1.5	24.00	75.42	16.67	1.67	6.25
2.	TS1127917	YARD	19.7	7	1.9	1.9	30.5	64.59	22.95	6.23	6.23
2	TS1127918	YARD	18.4	6.1	1.6	1.6	27.70	66.43	22.02	5.78	5.78
3	TS1127930	YARD	6	1.6	.1	.3	8.00	75.00	20.00	1.25	3.75
3	TS1127931	YARD	7.3	1.7	.3	.4	9.70	75.26	17.53	3.09	4.12
3	TS1127932	YARD	18.1	15.3	6	5.9	45.30	39.96	33.77	13.25	13.02
3	TS1127933	YARD	15.6	10.8	2.9	3.7	33.00	47.27	32.73	8.79	11.21
3	TS1127934	YARD	7.6 '	1,7	.3	.1	9.70	78.35	17.53	3.09	1.03
		MEAN	13.83	5.85	2.48	1.87	24.02	61.20	22.06	10.24	6.50
•	**	STD	5.46	4.20	1.94	1.68	11.33	12.50	8.43	10.16	3.32
		STD ERROR	2.23	1.71	.79	.68	4.63	5.10	3.44	4.15	1.36
	YARD DUP	MEAN	6.65	1.65	.20	.35	8.85	75.13	18.76	2.17	3.94
	COMPARISON		.65	.05	.10	.05	.85	.13	1.24	.92	.19
	CONFARISON			.03	.07	.03		.09	.87	.65	.13
		STD ERROR	.46	.04	.07	.04	.60	1 .09	.07	.65	. 13

# SIZE FRACTION DISTRIBUTION






Figure 4.1 Particle Size Distribution of Soil Less than 1/4 Inch in Diameter in the Tacoma Slag Study Exposure Zones




Figure 4.2 Relative Percent Composition of Elements in Driveway Slag at House 1




Figure 4.3 Relative Percent Composition of Elements in Driveway Slag at House 2




Figure 4.4 Relative Percent Composition of Elements in Driveway Slag at House 3




Figure 4.5 Relative Percent Composition of Elements in the EPA Vacuum Catch at House 2




Figure 4.6 Relative Percent Composition of Elements in the Household Vacuum Grab Samples at House 2




Figure 4.7 Relative Percent Composition of Elements in the Household Vacuum Grab Samples at House 3

Note the strong similarity between the chemical "fingerprint" of the slag in all three driveways with the dust collected in the EPA vacuum at House 2 (See Figures 4.2 through 4.5). The dust collected in the homeowner's vacuum contains a wider variety of chemical constituents (see Figures 4.6 and 4.7). More calcium was apparent in the homeowner's vacuum, and sulfur and chlorine were prominent in the household vacuum and absent in the EPA vacuum catch. It is likely that household vacuums catch more hair and skin from people and pets than the EPA vacuum. Animal and human hair and skin could account for calcium, sulfur and chlorine. Fireplace ash is another possible source of the chemical elements in the household vacuum. (All the houses had animals and fireplaces.) There are several other interesting trace metals in the household vacuum catch, such as zirconium, vanadium, manganese and bromine, that did not show up in the EPA vacuum catch.

One approach to comparison of chemical fingerprints is to examine ratios of arsenic and lead to indicator elements. Silicon is abundant in soils, and titanium is a somewhat constant trace constituent in soils. table 4.3 shows ratios in the chemical composition of slag and vacuum dust analyzed by XRF. Only the EPA vacuum sample collected in House 2 was similar to chemicals and chemical ratios in the slag in the driveway or to slag collected previously in the slag piles at the old ASARCO smelter.

Table 4.3
PERCENT ELEMENTAL COMPOSITION OF SLAG SAMPLES

	SLAG COARSE	SLAG FINE	DR SL1	DR SL2	DR SL3	HVS3	H VAC 2	H VAC 3
SI	14.1	15.8	12.6	12.0	18.2	12.6	5.5	8.4
TI	.3	.2	.3	.2	.3	.3	.3	.4
AS	1.9	2.5	1.7	4.6	1.7	1.6	> .1	> .1
PB	.9	1.3	1.0	1.2	1.1	.9	.1	> .1
SI/AS	7.5	6.3	7.4	2.6	11.0	8.0	163.9	503.9
SI/PB	15.8	12.3	12.7	10.3	16.4	13.9	108.3	262.2
TI/AS	.2	.1	.2	.1	.2	.2	9.7	21.4
TI/PB	.3	.2	.3	.2	.3	.3	6.4	11.1

SLAG COARSE = SOURCE SAMPLE TACOMA SMELTER COARSE (LESS  $10\mu\,g$ ) FRACTION SLAG FINE  $\approx$  SOURCE SAMPLE TACOMA SMELTER FINE (LESS THAN 2.5  $\mu\,g$ ) FRACTION AEROSOLIZED MATERIAL PASSING THROUGH 400 MESH SIEVE (LESS THAN  $38\mu\,g$ )

DR SL1 = HOUSE 1, TACOMA

DR SL2 = HOUSE 2, GIG HARBOR DR SL3 = HOUSE 3, TACOMA

HVS3 = EPA VAC HOUSE 2, GIG HARBOR

H VAC2 = HOUSE VAC HOUSE 2, GIG HARBOR

H VAC3 = HOUSE VAC HOUSE 2, GIG HARBOR

## 4.3 CMB Analysis of XRF Results

Chemical mass balance (CMB) models are useful tools for source apportionment of pollution sources and analysis of the chemical composition of the ambient air. They can also be used to relate the chemical composition of slag to house dust chemical composition. CMB analysis was applied to the XRF data collected in the driveways and in the household and EPA HVS3 catches. The individual results of this analysis are presented in Appendix B of this report. The driveway slag was modeled as a contributing source of lead, arsenic, sulfur, silicon, aluminum, calcium, and iron. Those same elements, along with their source inventory identification, are listed below:

- Tacoma road dust (TACRD)
- Tacoma soil (TACSD)
- Tacoma motor vehicle composite (TACMV)
- Tacoma leaded vehicles (TACPB)
- Kraft recovery mill (KRAFT)
- Tacoma wood combustion (TACWD)

Typically the CMB model is run in an iterative manner. Here indoor carpet dusts were modeled by trying single source profiles and combinations of source profiles such as driveway slag, road dust and wood combustion to determine the sources of the indoor dusts.

We found an almost perfect modeled fit using 13 chemicals in the dust collected using the HVS3 at House 2. Using only the House 2 driveway slag profile, the model explained 99.7% of the mass in the household dust (see Table 4.4). It is interesting that we were not able to fit combinations of the above sources, either from the driveway or our Tacoma source profile library, to either of the homeowners' vacuum dust samples. In fact, less than 40% of the mass in the household vacuums could be explained using the library of Tacoma sources or the current driveway slag.

## 4.4 Floor and Refrigerator Wipes

Tables 4.5 and 4.6 present the results obtained from refrigerator and floor wipe samples. The most noticeable difference was at House 3 for the refrigerator wipes. Unlike the other two houses, the surface sampled was a freezer in the ground level garage. Ground level sampling was consistently done at all homes; at House 3 the refrigerator was upstairs. Carpeted stairways form limiting barriers to tracked-in dust. Because of the stairs to the refrigerator in House 3, the freezer at ground level was used instead. The high concentrations of arsenic and lead on the top of the freezer in House 3 was duplicated in the sample duplicate on the same freezer. The higher concentration for sample 3 is likely due to its closer proximity to car exhaust and driveway dusts. The floor wipes in all cases had lower concentrations of both lead and arsenic.

## Table 4.4

## SOURCE CONTRIBUTION ESTIMATES (SCEs) FOR THE PARTICULATE LESS THAN 38 MICRONS IN THE HVS3 SAMPLE AT HOUSE 2 IN GIG HARBOR

	PLE DURA	TION	ION ESTIMATI 1.00 .12		HOUR	DATE: 99.7 12	SIZE:	VERS: FINE	ION: 7.0
so	OURCE * TYPE		SCE(UG/M3)	STD ER	R TSTA	ıτ			
12	HTSL	AG	.9970	.051	2 19.481	.4			
								•	
MEAS	URED CO	NCENT	RATION FINE	COARSE/TO	OTAL:				
	1.0+		.1/	.0+-	.0/	1.0+-	.1		
	UNCE	RTAIN	TY/SIMILARII	Y CLUSTE	RS VERSION	: 7.0	SUM OF CL	JSTER S	OURCES
					· · · · · · · · · · · · · · · · · · ·				
•			ATIONS - SI			TE:	VERSIO		
SAMP	LE DURA		• ••	START		00.7	SIZE:	FINE	
	R SQU		1.00 .12	PERCENT	DF	99.7 12			
								*	
SPEC	IES	I-·	MEAS		CALC	F	latio c/m²-	RAT	io r/u
1	TOT	T	1.00000+-	.10000	.99704+			.11	0
13	AL.	*	.01969+-	.00277	.01970+		1.00+-	.20	.0
14	SI	*	.12620+-	.01678	.12603+		1.00+-	.19	.0
15 16	P S	*	.00000< .00000<	.00007	.00000< >00000		.00< .00<	.00	.0 .0
17	CL	*	.00000<	.00133	.00000<		.00<	.00	.0
19	ĸ	*	.00419+-	.00048	.00387+		.92+-	.15	5
20	CA	*	.02479+-	.00280	.02262+-	.00254	.91+-	.15	6
22	TI	*	.00279+~	.00028	.00266+		.95+-	.13	3
23	V		.00000<	.00004	00000<		.00<	.00	.0
24 25	CR Mar		.00065+- .00000<	.00007	.00070+- .00000<		1.09+- .00<	.15 .00	.6 .0
25	MN FE	*	.17130+-	.01713	.16860+		.98+-	.14	1
28	NI .		.00000<	.00003	.00000<		.00<	.00	.0
29	CU		.01784+-	.00178	.01826+-		1.02+-	.14	.2
30	ZN	*	.00608+-	.00051	.00601+-	.00060	.99+-	.14	1
31	GA		.00000<	.00003	.00000<		.00<	.00	.0
33	ΑS	*	.01581+-	.00158	.01705+-		1.08+-	.15	.5
34 35	SE BR	*	.00000< .00000<	.00002	.00000< .00000<	.00001	.00<	.00 .00	.0 .0
37	RB		.00000<	.00002	.00000<	.00001	.00<	.00	.0
38	SR		.00009+-	.00002	.00012+-		1.31+-	.31	1.2
39	Y		.00000<	.00002	.00000<	00002	.00<	.00	.0
40	ZR		.00000<	.00003	.00000<	.00003	.00<	.00	.0
42	MO		.00143+-	.00014	.00139+-		.97+-	.14	2
46 47	PD		.00000<	.00013 .00016	.00003< .00000<	.00012 .00015	.00< .00<	.00	.1
48	AG CD		.00004<	.00016	.00031<	.00015	8.19< 3	.00 5.65	.0 1.2
49	IN		.00000<	.00017	.00000<	.00016	.00<	.00	.0
50	SN		.00010<	.00019	.00049<	.00018		B.72	1.5
51	SB		.00305+-	.00030	.00342+-		1.12+-	.16	.8
56	BA		.00100+-	.00068	.00000+-		.00+-	.63	-1.1
57	LA		.00137+-	.00093	.00111+-		.81+-	.83	2
80 82	HG		.00000<	.00004	.00000<	.00003	.00<	.00	.0
82	PB		.00906+-	.00091	-+00992. 	.00099	1.09+-	.15	.6

<sup>\*</sup>fitting species
\*\*calculated/measured

Table 4.5
REFRIGERATOR WIPE SAMPLES

HOUSE	ARSENIC ng/cm²	LEAD ng/cm²
1	1.8	30
2	3.2	7.8
3	580	580
3D	390	360

Table 4.6 FLOOR WIPE SAMPLES

HOUSE	ARSENIC ng/cm²	LEAD ng/cm²
1	.21	.8
2	.76	1.3
2D	.97	1.6
3	1.5	1.6

# 4.5 Analysis of Driveway Slag

The results in Table 4.7 show that both arsenic and lead concentrations increase with decreasing particle size in all three driveways. House 2 slag at Gig Harbor, which was farthest from the smelter, had the highest concentrations of lead and arsenic. House 2 also had the least weathered looking slag and possibly the least used driveway.

Table 4.7 DRIVEWAY SLAG

HOUSE		ARSENIC (	μg/g)		LEAD (μg/g)				
SIZE FRACTION(μm )	>180	>75	>38	<38	>180	>75	>38	<38	
1	2600	4200	6000	7000	1700	2300	3500	4200	
2	5000	13000	11000	19000	2600	4300	2900	4900	
3	2500	4200	6000	7100	1700	2700	4100	4600	

## 4.6 Analysis of Yard Soil

The concentrations of arsenic and lead in the yard soil is presented in Table 4.8. The samples are labeled A, B, C, and D to represent the assumed slag exposure regimes sampled where:

- A) indicates most likely part of the driveway from which slag could be tracked or leached onto the yard;
- B) indicates a location on a diagonal line from the driveway to a house entrance, no more than two feet from the driveway;
- C) indicates a location on a diagonal line from the driveway to the house or perpendicular to the driveway and no less than 18 feet from the driveway; and
- D) indicates a sheltered location on a diagonal line perpendicular to the end or side of the driveway and no less than 18 feet from the driveway.

At House 1, the lowest concentrations were found in a part of the yard that was a former garden. The highest concentrations of lead and arsenic were found in the location most removed from the slag driveway at House 1. Possibly paint from a nearby fence, drip line of the tree above, or some other contaminated source may have caused these high concentrations.

Yard soil at House 2 had the lowest levels of lead and arsenic. Grass in the yard at House 2 was luxuriant and had a deep sod layer. All four exposure regimes had similar lead and arsenic levels, but the concentration levels were lower in the less exposed locations (farthest from the driveway) than we expected.

Table 4.8 YARD SOIL

HOUSE		ARSENI	C (µg/g)			LEAD	(μg/g)	
SIZE FRACTION (µm)	>180	>75	>38	<38	>180	>75	>38	<38
1A	120	57	80	110	220	100	120	140
1B	120	120	150	200	230	210	210	200
1C	17	33	48	73	30	67	95	93
1D	120	100*	150	180	420	310*	460	450
2A	15.	22	25	84	45	60	75	31
2B	22	21	38*	27	47	48	91*	61
2C	16	18	23	29	30	32	43	53
2D	8.3	12	17	19	13	23	51	49
3A	60	55	490*	180*	69	65	67*	71*
3A dup	60	63	170*	62*	70	45	64*	100*
3B	63	49	150 🚋 .	100	87	48	43	54
3C	61	39	47	61	66	42	46	71
3D	50	42	81*	68*	55	55	630*	2300*

<sup>\*</sup>Small sample mass

Several of the numbers in Table 4.8 are marked with an asterisk. These are estimated values. The actual concentrations of arsenic and lead in these samples are uncertain because the small amount of sample available after sieving made the chemical analysis difficult.

These sample results can be compared to the background levels of arsenic and lead in urban areas which are about 20 ppm and 250 ppm, respectively. Becasue the locations sampled in this study are somewhat isolated from the typical urban environment, the background arsenic and lead in these soils might be expected to be lower than this. Also,

it should be kept in mind that these background measurements were made on soils that were not separated into smaller size fractions and represent an average of all of the arsenic and lead concentrations in all the particle sizes.

House 2 has the lowest levels for both lead and arsenic; a few of the arsenic in soil levels ar elevated above background. At House 1, most of the arsenic and a few of the lead samples are above background. House 3 has the highest levels of lead and arsenic. However, the values for lead that are above background in House 3 are estimated values.

### 4.7 Analysis of Vacuum Dust

The concentrations of arsenic and lead in the dust collected in the homeowner's vacuum cleaner were lower than those found in the yard soil except for House 2 (see Table 4.9). Lead concentrations for House 2 are two to four times higher indoors than in the yard soil. Highest concentrations of both arsenic and lead were clearly found in the smallest size fractions. This was noted in both household vacuum and EPA HVS3 vacuum catches (see Table 4.10).

Table 4.9 HOUSE VACUUM

HOUSE		ARSENIC (μ	g/g)			LEAD (μg/	3)	
SIZE FRACTION (μm)	>180	>75	>38	<38	>180	>75	>38	<38
1	50	55	70	ISF	85	140	180	ISF
2	75	69	110	170	180	120	150	200
3	24	86	110	ISF	33	40	61	ISF

ISF = insufficient sample

The highest concentrations of lead and arsenic were found in the EPA vacuum catches on the entry mat at House 2 and in the garage at House 3. The concentration per unit area is also presented in Table 4.10. The largest concentration tended to be in the

smallest size fraction. In the House 2 entry mat, the greater than 38 µm size range had higher arsenic than lead concentrations, reflecting the arsenic-to-lead ratios in slag.

## 4.8 Analysis of Ground Slag Samples

Table 4.11 presents a comparison of the effect of grinding on measured concentration of lead and arsenic. Aliquots from the size fraction (>180  $\mu$ m) were ground to a fine powder (<38  $\mu$ m). The measured concentrations in the ground sample of both arsenic and lead were nearly twice as high as in the original sample. The results suggest that when large particles in the driveway are ground up and pulverized by traffic, the availability of lead and arsenic increases significantly.

Table 4.10 **EPA VACUUM RESULTS** 

Н					ARSE	NIC							LE.	AD .			
U			SIZE FRACTION (μm)							SIZE FRACTION (µm)							
S E	SURFACE	>	180	>	75		-38	,	<38	>	180		>75		>38		<38
		μg/g	μg/cm²	µ g/g	μg/cm²	μg/g	μg/cm²	μg/ g	μg/cm²	μg/g	μg/cm²	μ <b>g</b> /g	μg/cm²	μg/ 9	μg/cm²	μg/g	μg/cm²
1	CARPET	95	<.01	49	<.01	180	<.01	120	<.01	230	.01	170	<.01	72	<.01	270	<.01
2	CARPET	180	.01	140	.02	230	.12	360	.17	110	.01	190	.03	250	. 13	250	.12
2	MAT	520	.07	290	.01	460	.23	690	.47	240	.03	150	<.01	210	.10	290	.20
3	ENTRY*	300	.03	580	<.01	250	.03	300	.01	160	.02	500	<.01	220	.03	280	.01
3	CARPET	150	<.01	95	<.01	190	<.01	380	<.01	130	<.01	130	<.01	270	.01	500	<.01
3	GARAGE	240	.02	ISS	<.01	180	<.01	390	.02	190	<.01	188	<.01	230	.01	400	<.01

The calculation of concentration per unit area is presented in Appendix A.

<sup>\*</sup>Carpet was less than six months old.

Table 4.11
COMPARISON OF CONCENTRATIONS IN
GROUND AND UNGROUND STATE

Before	Grinding	Afte	er Grinding

Driveway Location	As μg/g	Pb µg/g	As μg/g	Pb µg/g
House 1	2600	1700	5000	3300
House 2	5000	2600	11000	4100
House 3	2500	1700	4300	3200

# 4.9 Method Validation and Quality Control

## 4.9.1 Analysis of Field Duplicates

Duplicate samples were collected to determine the representativeness of the sampling locations. Table 4.12 shows a comparison of duplicate sample collected on refrigerators, floors, and at one yard sampling location. A large difference is notable on the refrigerator (freezer) wipe at House 3. The concentrations in both the sample and duplicate sample are about 100 times larger than the wipes of refrigerators at Houses 1 and 2. The difference between the sample and the duplicate is about a 50% difference, and is probably related to proximity to sources of the two locations. The largest concentrations were on the side of the freezer nearest to the car and driveway. This also may have been due to other exposure differences across the top of the freezer.

The floor wipes at House 2 show good agreement between sample and duplicate of measured concentrations of lead and arsenic.

The yard soil duplicate comparison also suggests that the sampling techniques provide representative results when a large enough sample is available. Larger differences between samples and duplicate samples were noted in the two smallest size fractions.

Table 4.12

COMPARISON OF LEAD AND ARSENIC CONCENTRATIONS MEASURED BY DUPLICATE SAMPLES

LOCATION	REFRIGERATO	OR WIPES				
	As μg/cm²	Pb μg/cm²				
House 3	580	580				
Duplicate	390	360				
RPD	39.2	46.8				
	FLOOR	WIPE				
House 2	0.76	1.3				
Duplicate	0.97	1.6				
RPD	24.3	20.7				
·	YARD SOIL					
	As μg/g	Pb μg/g				
House 3 (>180 μm)	60	69				
Duplicate	60	70				
RPD	0	1.4				
House 3 (>75 μm)	55	65				
Duplicate	63	45				
RPD	13.6	36.3				
House 3 (>38 μm)	490*	67*				
Duplicate	170*	64*				
RPD	145.4	4.6				
House 3 (38 μm)	180*	71*				
Duplicate	62*	100*				
RPD	97.5	10.4				

<sup>\*</sup> Small simple size (< 0.3 grams) RPD = Relative percent difference

Table 4.13 presents results for blanks and rinses collected in this field study. The rinses in all but EPA vacuum rinses were the final distilled water rinse after the equipment was thoroughly cleaned. These rinses were used as a field blank. However, the rinse of EPA vacuum were acetone-pentane rinses to collect particles remaining in the vacuum and catch bottle, and thus are not really a blank, but rather the remainder of the vacuum catch. These numbers should not be subtracted from the concentrations in the HVS3 catch, but could be added to those numbers. They were not added to catch in the HVS3.

## 4.9.2 Quality Assurance/Quality Control

The quality assurance/quality control (QA/QC) program for the Tacoma Slag study included the following QC elements:

- Blanks, calibration standards, and calibration check standards
- Laboratory duplicates
- Predigestion matrix spikes
- Postdigestion analytical spikes
- Blind standard reference materials (SRMs) sent from the field.

The satisfactory analysis of blanks, calibration standards, and calibration check standards is part of and precedes the analysis of any samples. Instruments are considered calibrated and ready for analysis if the correlation coefficient of the calibration curve is at least 0.995, and if the recovery of the calibration check standard is within the range of 90–110%.

Table 4.13
BLANK AND RINSE ANALYSIS

FLOOR AND REFRIGERATOR BLANKS								
	Field Blank	Trip Blank						
As	< 0.00 mg/cm <sup>2</sup>	< 0.00 ng/cm <sup>2</sup>						
Pb	0.16 ng/cm <sup>2</sup>	0.16 ng/cm <sup>2</sup>						
	SOIL SAMPLE BUCKET TRIP BLANK							
As	1.6 μg							
Pb	4.9 μg							
ļ 	SOIL CORER RINSE AFTER HOUSE 1							
As	0.05 μg							
Pb	0.14 μg							
	SPAT	ULA RINSE AFTER HOUSE 2						
As	0.76 μg							
Pb	0.1 μg							
	SOIL C	ORER RINSE AFTER HOUSE 2						
As	< .05 μg	·						
Pb	< .01 μg							
	SOIL C	ORER RINSE AFTER HOUSE 3						
As	< .05 μg							
Pb	< .01 μg							
	SPAT	ULA RINSE AFTER HOUSE 3						
As	0.24 μg							
Pb	0.27 μg							
	SHOVE/RIN	ISE BETWEEN DRIVEWAY 2 AND 3						
As	1.6 μg							
Pb	1.2 μg							

Table 4.13

# (Continued)

Н	IOUSE 1 EPA VACUUM RINSE AFTER RUG SAMPLE COLLECTION						
As	7.5 μg						
Pb	20 μg						
Н	HOUSE 2 EPA VACUUM RINSE AFTER RUG SAMPLE COLLECTION						
As	60 µg						
Pb	35 μg						
HOUSE 2 EPA VACUUM RINSE AFTER FLOOR MAT SAMPLE COLLECTION							
As	$120~\mu\mathrm{g}$						
Pb	50 μg						
HOUSE 3 EPA VACUUM RINSE AFTER ENTRY SAMPLE							
As	45 μg						
Pb	38 μg						
HOUSE 3 EPA VACUUM RINSE AFTER FAMILY RM SAMPLE COLLECTION							
As	55 μg						
Pb	70 μg						
HOUSE 3 EPA VACUUM RINSE AFTER CARPORT							
As	26 μg						
Pb	32 μg						

Duplicates provide a means for estimating precision. The duplicates are created by splitting a given sample before any sample preparation procedures are begun. The precision QC statistic is the relative percent difference (RPD), defined in Section 3. The results of the analysis of duplicates are summarized in Table 4.14. For aqueous samples, the EPA considers  $\pm 20\%$  RPD to be an acceptable precision. For soils, the EPA uses this same value as a target precision, but considers acceptable RPDs up to  $\pm 35\%$ . All of the RPDs listed in Table 4.14 are well within these guidelines.

Table 4.14
RESULTS OF THE ANALYSIS OF LABORATORY DUPLICATES

Sample Matrix	No. of Duplicates	RPD or AVG. RPD (%) Arsenic Lead		
Water Rinse	1 As/1 Pb	1.2 0		
Water/Acetone Rinse	2 As/2 Pb	3.2 2.4		
Wipe	2 As/3 Pb	4.8 1.4		
Soil (ICP)	11 As/14 Pb	$3.1 \pm 2.7$ $2.8 \pm 2.5$		
Soil (GFAA)	10 As/6 Pb	$2.1 \pm 1.9  0.9 \pm 0.8$		

Accuracy of the laboratory results can be estimated by the analysis of preand post-digestion spikes. The pre-digestion spikes are created by splitting a given sample before sample preparation and adding known amounts of pure element standards to one of the sample splits. The post-digestion spikes are created by adding known amounts of pure element standards to a sample digestate after the sample has been analyzed. The QC statistic is the percent recovery (%R). The results of the analysis of both types of spikes are summarized in Table 4.15. For aqueous samples and soils, the EPA considers an acceptable spike recovery range to be 75-125%. All of the percent recoveries using EPA Method 3050 digestion listed in Table 4.15 are well within these guidelines.

Table 4.15
RESULTS OF THE ANALYSIS OF SPIKED SAMPLES

Sample Matrix	Spike	Spike No. of Spikes		% Recovery or Avg. % Recovery Arsenic Lead		
Water Rinse	Pre	2 As/2 Pb	99.5	105.5		
	Post	1 As/1 Pb	101	96		
Water/Acetone Rinse	Post	2 As/2 Pb	86.4	97		
Wipe	Post	2 As/2 Pb	90	102		
Soil (ICP)	Pre	5 As/5 Pb	97.8	95.6		
	Post	11 As/11 Pb	96.6	95.0		
Soil (GFAA)	Pre	2 As/1 Pb	94	108		
	Post	2 As/2 Pb	88.4	96.0		

A further check of accuracy is the analysis of sample reference materials (SRMs) sent blind from the field. The results of the analysis of blind solid SRMs are summarized in Table 4.16. There are no EPA guidelines for the percent recovery of field solid SRMs, because agency-approved digestions are strong-acid extractions designed to extract metals that are bio-available. SRMs are certified for total metals only. Thus, the results obtained via EPA digestions can vary considerably from the certified values, most often (but not always) being lower. All of the arsenic recoveries and two of the lead recoveries were within 69–92%. Two of the lead recoveries were low. Considering the excellent spike recoveries discussed above, it is unlikely that the poor SRM recoveries were due to analytical error. Most likely, the low recoveries are due to a combination of the poor digestion efficiency of the method and unavoidable matrix effects.

Table 4.16 STANDARD REFERENCE MATERIALS ANALYSIS RESULTS

	Arsenic			Lead		
SRM	Result	. Given	%R	Result	Given	%R
CBS CCN-1	240	260 <u>+</u> 20	92.3	27,000	74,500 <u>+</u> 500	36.2
CBS SO-2	0.83	1.2 <u>+</u> 0.2	69.2	5.4	21 <u>+</u> 4	25.7
CBS PO-1	7000	7700 <u>+</u> 300	90.9	23,000	27,500 <u>+</u> 200	83.6
NBS 1648	83	115 <u>+</u> 10	72.2	5,400	6,550 <u>+</u> 80	82.4

CBS = Canadian Bureau of Standards

NBS = National Bureau of Standards

#### 5.0 CONCLUSIONS AND RECOMMENDATIONS

This study was designed to sample dust, soil and slag at three selected homes in Tacoma and Gig Harbor, Washington. These homes have driveways surfaced with slag from the ASARCO copper smelter in Ruston. The slag contains arsenic and lead at concentrations greater than 2500 and 1500 ppm respectively. Residences more than four miles from the smelter with slag-covered driveways were selected to investigate the possibility that driveway slag was the major source of arsenic and lead at outdoor and indoor locations at each of these residences. We know that baseline levels of arsenic and lead exist in urban areas. It was postulated that residences closer to the smelter would have notable buildups of chemicals from the historical smelter emissions and thus would deviate from our study model, which calls for one source and several recipient areas of arsenic and lead particulates.

Dusts and soil particles from outdoors (soil and driveway dusts) were compared to indoor dusts, using a chemical mass balance (fingerprinting) technique. Four particle size fractions were analyzed, where samples were sufficient, to investigate arsenic and lead concentrations as a function of particle size. Furthermore, particles smaller than 150 microns were analyzed chemically because they can adhere to the hands of children. Indoor samples were taken from kitchen floors, living room carpets, and tops of refrigerators to assess current to long-term buildups of arsenic and lead at the selected homes.

The sampling strategy was designed to measure arsenic and lead levels in driveway slag material and at locations close to slag-covered driveway surfaces, as well as away from the driveways, in order to assess migrations of arsenic and lead from the driveway source area. Soil samples close to the driveway and far from it, as well as from indoor mats and carpets, were taken to investigate track-in concepts.

The conclusions for the study follow:

- There was a very strong correlation between lead and arsenic in driveway slag and in household carpet dusts at one residence. Unfortunately, sufficient carpet dusts for chemical fingerprinting were collected at only one residence -- a special EPA vacuum device for carpets obtained smaller samples than was planned. Chemical mass balance analyses of source (slag) and receptor (carpet) dust at this house showed that 99% of the arsenic and lead concentrations in the dust came from one source: slag from the driveway.
- Concentrations of arsenic and lead were 10 to 20 times greater in driveway slag than in the household carpet dusts. Concentrations in the carpet dusts collected by the EPA sampler varied from 49 to 690 ppm for arsenic and from 72 to 500 ppm for lead. Some of these concentrations in dust are much higher than would be expected given the arsenic and lead levels in urban background soils (20 ppm for arsenic and 250 ppm for lead).
- The highest concentrations for both lead and arsenic were found on entry mats and in a carport. Concentrations of these chemicals in entry mats were often more than twice the interior living room carpet dust levels. This suggests that entry mats are moderately effective as interceptors of tracked-in slag and soil dusts. This also restates the obvious, that the bulk of tracked-in outdoor dusts are located at residential entrances.
- Dust removed from each homeowner's vacuum cleaner resulted in considerable dust, dirt and debris as a result of the general usage of the device in the home and possibly the car and garage. It was, however, found that the special EPA vacuum cleaner was a superior dust collection device for this study because only known carpeted areas were sampled and household debris was not collected.

- The EPA vacuum device was configured to sample only the dust near the
  carpet surface and not the deep-seated dusts tracked in from prior years. It
  can thus be concluded that results from this study report conclusions for
  current residential dust conditions.
- Indoor dust samples were collected from the tops of refrigerators or a freezer and from kitchen floor linoleum at each home. Arsenic and lead concentrations present in these samples indicate the presence of a source or sources for lead and arsenic in the area. However, because of the small amounts of collected dusts, it was not possible to compare these samples to driveway slag materials using the source fingerprinting methods to quantitate source ratios.
- Concentrations of lead and arsenic in the yard soil varied from below local urban background levels (about 20 ppm for arsenic and 250 ppm for lead) to well above these levels.
- Driveway surface materials ranged in size from about one-half inch to about three inches. However, below the surface layer of slag, smaller dust-sized materials were found at each residence. Under vehicular and foot traffic, the grinding of surface chunks of slag and the compression of smaller particles below the surface may be the means by which slag dusts continue to be available for track-in to the homes and across the yards.
- For slag materials and carpet dusts where sufficient material was collected, clearly higher arsenic and lead concentrations were observed with the smaller particle sizes. The extent of this apparent enrichment was greatest for slag where the smallest particulate concentrations (less than 38 microns) ranged to 19,000 ppm for arsenic and 4,900 ppm for lead. Enrichment for the same smallest particles in carpet dusts ranged up to 690 ppm for arsenic and

500 ppm for lead. In yard soil, there was less enrichment in the smallest particulate sizes.

- The largest size fractions (< 180 microns) dealt with in this study from the slag and carpet dusts were consistently greater than background arsenic levels.
- The study found a factor of two increase in the concentrations of arsenic and lead by grinding and pulverizing 180 micron or greater-sized particles to a diameter less than 38 microns. These results may be due to an increased availability of arsenic and lead in these samples as a result of increased surface area and enhanced chemical digestibility in the laboratory. An additional explanation is that once the surface (oxide) coating on slag is broken, additional chemicals may then be released.

After review of the data and procedures used to collect information, we have several recommendations for future studies:

- The amount of driveway slag collected was more than adequate. One 5-gallon bucket per driveway will be adequate for future sampling, rather than collecting two buckets as collected for this study. Screening out slag chunks in the field will also save time in the future.
- A composite surface soil sample from each yard would be needed for future studies if fingerprinting studies are designed to include source contributions from yard soil materials.
- The EPA vacuum (HVS3) can collect dust particles smaller than 150 microns
  without collecting household debris. It is thus a necessary field sampling
  device for studies of this type. However, larger surface areas need to be
  sampled to obtain sufficient sample amounts for laboratory analysis.

- To explain the sources of dust in the homeowner's vacuum cleaner using receptor modeling, several additional source profiles would be needed. These include household chemicals such as carpet cleaners and deodorants, furnace dusts and possible discarded dermal material. Outside source profiles would include yard soils, as noted above, and street and road dusts.
- It would be valuable to sample a baseline control home without a slagsurfaced driveway in the Tacoma-Ruston and Gig Harbor areas, as well as a background level control home which is away from any smelter influence. Such controls would allow comparison of study results to those obtained for control homes.

#### 6.0 BIBLIOGRAPHY AND REFERENCES

Barley, G., 1981: "Air Quality and Respiratory Health: A Comparison Study of Two Health Contaminants," Masters Thesis, University of Washington, Seattle.

Black and Veatch, 1988: "Endangerment Assessment, Ruston/Vashon Island, Technical Memorandum", State of Washington Department of Ecology, Olympia, Washington.

Bowen, H.J.M., 1966: <u>Trace Elements in Biochemistry</u>, Academic Press, New York, 241 pp.

Cooper, J.A., et al., 1984: "Applications of Receptor Modeling Methods to Source Apportionment of Arsenic in the Ruston-Tacoma, Washington Airshed: A Feasibility Study," NEA, Inc., Beaverton, Oregon, 59 pp.

Davidson, C.L. and Elias, R.W., 1986: "Environmental concentrations and potential pathways to human exposure," in <u>Air Quality Criteria for Lead</u>, U.S. EPA, Research Triangle Park.

Davies, D.J.A, et al., 1990: "Relationships between blood lead and lead intake in two-year-old urban children in the U.K.," <u>Science of the Total Environment</u>, <u>90</u>, p. 13-29.

National Academy of Sciences, 1977: <u>Arsenic</u>, National Academy of Sciences Publication, Washington, DC, 332 pp.

Ibid., 1972: <u>Lead: Biological Effects of Atmospheric Pollutants</u>, National Academy of Sciences Publication, Washington, DC, 330 pp.

Roberts, J.W., 1991: Personal Communication.

Roberts, J.W., et al., 1991: "Reducing lead exposure from remodeling and soil track-in in older homes," <u>Proceedings of Air & Waste Management Association Annual Meeting</u>, Vancouver, B.C. In press.

Ibid., 1990: "Development and testing of a high volume sampler for pesticides and toxics in dust," <u>Toxicology and Industrial Health</u>, 8, .1

Ibid., 1990: "Monitoring and controlling lead in house dust in older homes," in Vol. 2: <u>Indoor Air '90: Proc. 5th International Conf. on Indoor Air and Climate</u>, pp. 425-430, Canada Mortgage and Housing Corp., Ottawa.

## APPENDIX A

LABORATORY ANALYSIS REPORT (TABLE A.1)

QUALITY ASSURANCE REPORT (TABLE A.2)

CALCULATION (TABLE A.3)

Page: 1

Client Name: Tacoma Slag Study

Date Received: 1/4/91

Report Date: 1/18/91 Project Number: 316/001

NEA ID: 91-S1

Client ID: TS 1127904-C

Sample Mass:

0.4993 grams

Extraction Volume:

25.0 mL

Analyte

Result

Date Analyzed

As Pb

70 180 ug/gram ug/gram

1/18/91 1/18/91

NEA ID: 91-S2

Client ID: TS 1127939-D

Sample Mass:

0.4959 grams

Extraction Volume:

25.0 mL

Analyte

Result

Date Analyzed

As Pb

NEA ID: 91-S3

66 110

ug/gram ug/gram. 1/18/91 1/18/91

Client ID: TS 1127906-7-A

Sample Mass:

0.5004 grams

Extraction Volume:

25.0 mL

Analyte

Result

Date Analyzed

As Pb 2600 1700

ug/gram ug/gram 1/18/91 1/18/91

NEA ID: 91-S4

Client ID: TS 1127906-7-AG

Sample Mass:

0.4992 grams

Extraction Volume:

25.0 mL

Analyte

Result

Date Analyzed

As Pb 4200 2300 ug/gram ug/gram 1/18/91 1/18/91

NEA ID: 91-S5

Client ID: TS 1127906-7-C

Sample Mass:

0.5029 grams

Extraction Volume:

25.0 mL

Analyte

Result

Date Analyzed

As

6000

ug/gram

1/18/91

Pb

3500

ug/gram

1/18/91

Page: 2

Client Name: Tacoma Slag Study Report Date: 1/18/91

Date Received: 1/04/91 Project Number: 316/001

NEA ID: 91-S6 Client ID: TS 1127906-7-D

Sample Mass: 0.4996 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 7000 ug/gram 1/18/91 Pb 4200 ug/gram 1/18/91

NEA ID: 91-S7 Client ID: TS 1127950-1-A

Sample Mass: 0.4959 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 5000 ug/gram 1/18/91 Pb 2600 ug/gram 1/18/91

NEA ID: 91-S8 Client ID: TS 1127950-1-AG

Sample Mass: 0.3941 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 11000 ug/gram 1/18/91 Pb 4100 ug/gram 1/18/91

NEA ID: 91-S9 Client ID: TS 1127950-1-B

Sample Mass: 0.4961 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 13000 ug/gram 1/18/91 Pb 4300 ug/gram 1/18/91

NEA ID: 91-S10 Client ID: TS 1127950-1-C

Sample Mass: 0.4929 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 11000 ug/gram 1/18/91 Pb 2900 ug/gram 1/18/91

Page: 3

1/18/91 Client Name: Tacoma Slag Study Report Date:

Date Received: 1/04/91 Project Number: 316/001

Client ID: TS 1127953-4-A NEA ID: 91-S11

Sample Mass: 0.4956 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

2500 1/18/91 Αs ug/gram Pb 1700 1/18/91 ug/gram

NEA ID: 91-S12 Client ID: TS 1127953-4-AG

Sample Mass: 0.5006 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

4300 1/18/91 As ug/gram 3200 Pb 1/18/91 ug/gram

Client ID: TS 1127953-4-B NEA ID: 91-S13

Sample Mass: 0.4926 grams Extraction Volume: 25.0 mL

Result Analyte Date Analyzed

4200 1/18/91 As ug/gram Рb 2700 1/18/91 ug/gram

NEA ID: 91-S14 Client ID: TS 1127953-4-C

Sample Mass: 0.4987 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

6000 As ug/gram 1/18/91 Pb 4100 ug/gram 1/18/91

Client ID: TS 1127906-7-AG NEA ID: 91-S15

0.4974 grams Extraction Volume: Sample Mass: 25.0 mL

Result Analyte Date Analyzed As 5000 ug/gram 1/18/91

Pb 3300 ug/gram 1/18/91

Page: 4

Client Name:

Tacoma Slag Study

Report Date:

1/18/91

Date Received:

01/04/91

Project Number:

316/001

NEA ID: 91-S16

Client ID: TS 1127950-1-D

Sample Mass:

0.4936 grams

Extraction Volume:

25.0 mL

Analyte

Result

Date Analyzed

As Pb 19000 4900 ug/gram ug/gram 1/18/91

1/18/91

NEA ID: 91-S17

Client ID: TS 1127953-4-D

Sample Mass:

0.4962 grams

Extraction Volume:

25.0 mL

Analyte

Result

Date Analyzed

As Pb 7100 4600 ug/gram ug/gram 1/18/91 1/18/91

Page: 1

Client Name: Tacoma Slag Study Report Date: 1/18/91
Date Received: Project Number: 316/001

NEA ID: 90-S22 Client ID: TS 1127901

Sample Area: 645 cm2 Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 1.8 ng/cm2 12/20/90 Pb 30 ng/cm3 12/31/90

NEA ID: 90-S23 Client ID: TS 1127902

Sample Area: 2580 cm2 Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 0.21 ng/cm2 12/20/90 Pb 0.80 ng/cm2 12/31/90

NEA ID: 90-S24 Client ID: TS 1127903-A

Sample Mass: 0.5271 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 95 ug/gram 1/02/91 Pb 230 ug/gram 1/02/91

NEA ID: 90-S25 Client ID: TS 1127903-B

Sample Mass: 0.1428 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 49 ug/gram 1/02/91 Pb 170 ug/gram 1/02/91

NEA ID: 90-S26 Client ID: TS 1127903-C

Sample Mass: 0.2300 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

Pb 180 ug/gram 1/02/91 As 72 ug/gram 1/02/91

Page:

Client Name: Tacoma Slag Study Report Date: 1/18/91 316/001

Project Number: Date Received:

Client ID: TS 1127903-D NEA ID: 90-S27

Extraction Volume: 25.0 mL 0.0289 grams Sample Mass:

Analyte Result Date Analyzed

1/02/91 120 ug/gram As-270 1/02/91 Pb ug/gram

NEA ID: 90-S34 Client ID: TS 1127908-A

0.4817 grams Extraction Volume: 25.0 mL Sample Mass:

Analyte Result Date Analyzed

1/09/91 As 120 ug/gram 1/09/91 Pb 220 ug/gram

Client ID: TS 1127908-B NEA ID: 90-S35

0.5225 grams Extraction Volume: 25.0 mL Sample Mass:

Analyte Result Date Analyzed

57 1/09/91 ug/gram As 100 1/09/91 Pb ug/gram

NEA ID: 90-S36 Client ID: TS 1127908-C

Sample Mass: 0.4980 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

80. 1/09/91 ug/gram Pb 120 ug/gram 1/09/91

NEA ID: 90-S37 Client ID: TS 1127908-D

0.4920 grams Sample Mass: Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

1/09/91 As 110 ug/gram 140 Pb ug/gram 1/09/91

Page:

01/18/91 Client Name: Tacoma Slag Study Report Date:

Project Number: 316/001 Date Received:

Client ID: TS 1127909-A NEA ID: 90-S39

25.0 mL 0.4825 grams Extraction Volume: Sample Mass:

Date Analyzed Analyte Result

As 120 ug/gram 1/09/91 230 1/09/91 Pb ug/gram

Client ID: TS 1127909-B NEA ID: 90-S40

0.5407 grams Extraction Volume: 25.0 mL Sample Mass:

Analyte Result Date Analyzed

120 1/09/91 ug/gram As 1/09/91 Рb 210 ug/gram

NEA ID: 90-S41 Client ID: TS 1127909-C

0.5087 grams Extraction Volume: 25.0 mL Sample Mass:

Analyte Result Date Analyzed

1/09/91 150 ug/gram As 210 1/09/91 Pb ug/gram

Client ID: TS 1127909-D NEA ID: 90-S42

0.5446 grams Extraction Volume: 25.0 mL Sample Mass:

Analyte Result Date Analyzed

1/09/91 As 200 ug/gram 200 1/09/91 Pb ug/gram

Page:

Report Date: 1/18/91 Client Name: Tacoma Slag Study Project Number: 316/001 Date Received: NEA ID: 90-S44 Client ID: TS 1127910-A 0.5304 grams Extraction Volume: 25.0 mL Sample Mass: Analyte Result Date Analyzed 17 ug/gram 1/09/91 As Рb 30 1/09/91 ug/gram Client ID: TS 1127910-B NEA ID: 90-S45 Sample Mass: 0.5221 grams Extraction Volume: 25.0 mL Analyte Result Date Analyzed 33 1/09/91 As ug/gram Pb 67 1/09/91 ug/gram NEA ID: 90-S46 Client ID: TS 1127910-C 0.5004 grams Extraction Volume: 25.0 mL Sample Mass: Analyte Result Date Analyzed 48 1/09/91 As ug/gram Pb 95 1/09/91 ug/gram

NEA ID: 90-S47 Client ID: TS 1127910-D

Sample Mass: 0.5122 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 73 ug/gram 1/09/91 Pb 93 ug/gram 1/09/91

NEA ID: 90-S49 Client ID: TS 1127911-A

Sample Mass: 0.4983 grams Extraction Volume: 25.0 mL

 Analyte
 Result
 Date Analyzed

 As
 120
 ug/gram
 1/09/91

 Pb
 420
 ug/gram
 1/09/91

Page: 5

Client Name: Tacoma Slag Study Report Date: 1/18/91 Date Received: Project Number: 316/001

NEA ID: 90-S50 Client ID: TS 1127911-B

Sample Mass: 0.0450 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 100 ug/gram 1/09/91 Pb 310 ug/gram 1/09/91

NEA ID: 90-S51 Client ID: TS 1127911-C

Sample Mass: 0.5039 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 150 ug/gram 1/09/91 Pb 460 ug/gram 1/09/91

NEA ID: 90-S52 Client ID: TS 1127911-D

Sample Mass: 0.4875 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 180 ug/gram 1/09/91 Pb 450 ug/gram 1/09/91

NEA ID: 90-S54 Client ID: TS 1127013-A

Sample Mass: 0.5154 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 15 ug/gram 1/09/91 Pb 45 ug/gram 1/09/91

NEA ID: 90-S55 Client ID: TS 1127013-B

Sample Mass: 0.4960 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 22 ug/gram 1/09/91 Pb 60 ug/gram 1/09/91

6 Page:

1/18/91 Tacoma Slag Study Report Date: Client Name:

Project Number: 316/001 Date Received:

NEA ID: 90-S56 Client ID: TS 1127013-C

Sample Mass: 0.5011 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

25 1/09/91 ug/gram As Pb 75 ug/gram 1/09/91

NEA ID: 90-S57 Client ID: TS 1127013-D

Sample Mass: 0.5030 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

1/09/91 Pb 84 ug/gram As 31 ug/gram 1/09/91

NEA ID: 90-S58 Client ID: TS 1127914-A

0.4913 grams Extraction Volume: 25.0 mL Sample Mass:

Analyte Result Date Analyzed

22 1/09/91 As ug/gram 1/09/91 Pb 47 ug/gram

NEA ID: 90-S59 Client ID: TS 1127914-B

0.5220 grams Extraction Volume: 25.0 mL Sample Mass:

Date Analyzed Analyte Result

As 21 ug/gram 1/09/91 48 1/09/91 Pb ug/gram

NEA ID: 90-S60 Client ID: TS 1127914-C

Sample Mass: 0.2088 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

38 ug/gram 1/09/91 As 91 ug/gram 1/09/91 Pb

Page: 7

Client Name: Tacoma Slag Study Report Date: 1/18/91
Date Received: Project Number: 316/001

NEA ID: 90-S61 Client ID: TS 1127914-D

Sample Mass: 0.4884 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 27 ug/gram 1/09/91 Pb 61 ug/gram 1/09/91

NEA ID: 90-S62 Client ID: TS 1127917-A

Sample Mass: 0.4988 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 16 ug/gram 1/14/91 Pb 30 ug/gram 1/14/91

NEA ID: 90-S63 Client ID: TS 1127917-B

Sample Mass: 0.5086 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 18 ug/gram 1/14/91 Pb 32 ug/gram 1/14/91

NEA ID: 90-S64 Client ID: TS 1127917-C

Sample Mass: 0.4940 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 23 ug/gram 1/14/91

Pb 43 ug/gram 1/14/91

NEA ID: 90-S65 Client ID: TS 1127917-D

Sample Mass: 0.5163 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 29 ug/gram 1/14/91 Pb 53 ug/gram 1/14/91

8 Page:

Report Date: 1/18/91 Client Name: Tacoma Slag Study

Project Number: 316/001 Date Received:

Client ID: TS 1127918-A NEA ID: 90-S66

Extraction Volume: 25.0 mL Sample Mass: 0.5150 grams

Analyte Result Date Analyzed

8.3 1/14/91 As ug/gram 13 Pb ug/gram 1/14/91

NEA ID: 90-S67 Client ID: TS 1127918-B

Sample Mass: 0.4933 grams Extraction Volume: 25.0 mL

Date Analyzed Analyte Result

12 1/14/91 As ug/gram Pb 23 1/14/91 ug/gram

NEA ID: 90-S68 Client ID: TS 1127918-C

Extraction Volume: 25.0 mL 0.4937 grams Sample Mass:

Analyte Result Date Analyzed

1/14/91 As 17 ug/gram Pb 51 1/14/91 ug/gram

NEA ID: 90-S69 Client ID: TS 1127918-D

0.5064 grams Extraction Volume: 25.0 mL Sample Mass:

Analyte Result Date Analyzed

19 1/14/91 As ug/gram Pb 49 1/14/91 ug/gram

NEA ID: 90-S80 Client ID: TS 1127921

Sample Area: 645.000 cm2 Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

3.2 12/20/90 As ng/cm2 Pb 7.8 ng/cm2 12/31/90

Page: 9

1/03/91

Report Date: 1/18/91 Client Name: Tacoma Slag Study Project Number: 316/001 Date Received: NEA ID: 90-S81 Client ID: TS 1127922 Extraction Volume: 25.0 mL 2580 cm2 Sample Area: Result Date Analyzed Analyte 0.76 ng/cm2 12/20/90 As 1.3 12/31/90 PЪ ng/cm2 NEA ID: 90-S82 Client ID: TS 1127923 Sample Area: 2580 cm2Extraction Volume: 25.0 mL Date Analyzed Analyte Result 12/20/90 < 0.01 ng/cm2 As 12/31/90 0.16 ng/cm2 NEA ID: 90-S83 Client ID: TS 1127924 Extraction Volume: 25.0 mL Sample Area: 2580 cm2 Result Date Analyzed Analyte 0.97 12/20/90 ng/cm2 As

NEA ID: 90-S84 Client ID: TS 1127925-A

1.6

Pb

Sample Mass: 0.4998 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

ng/cm2

As 75 ug/gram 1/14/91 Pb 80 ug/gram 1/14/91

NEA ID: 90-S85 Client ID: TS 1127925-B

Sample Mass: 0.5080 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 69 ug/gram 1/14/91 Pb 120 ug/gram 1/14/91

Page: 10

Tacoma Slag Study Report Date: 1/18/91 Client Name: Date Received: Project Number: 316/001 NEA ID: 90-S86 Client ID: TS 1127925-C Extraction Volume: 25.0 mL 0.4921 grams Sample Mass: Date Analyzed Result Analyte 1/14/91 ug/gram 110 150 1/14/91 Pb ug/gram NEA ID: 90-S87 Client ID: TS 1127925-D 0.4941 grams 25.0 mL Sample Mass: Extraction Volume: Result Date Analyzed Analyte 170 1/14/91 As ug/gram 200 1/14/91 Pb ug/gram NEA ID: 90-S88 Client ID: TS 1127926-A 0.4995 grams Extraction Volume: 25.0 mL Sample Mass: Result Date Analyzed Analyte 180 1/02/91 As ug/gram 110 1/02/91 Pb ug/gram NEA ID: 90-S89 Client ID: TS 1127926-B Sample Mass: 0.5089 grams Extraction Volume: 25.0 mL Result Date Analyzed Analyte 1/02/91 140 ug/gram 1/02/91 Pb 190 ug/gram NEA ID: 90-S90 Client ID: TS 1127926-C Sample Mass: 0.5177 grams Extraction Volume: 25.0 mL

Analyte

As

Pb

Result

ug/gram

ug/gram

230

250

Date Analyzed

1/02/91

1/02/91

Page: 11

Client Name: Tacoma Slag Study

Date Received:

Report Date: 1/18/91 Project Number: 316/001

NEA ID: 90-S91

Client ID: TS 1127926-D

Sample Mass:

0.5243 grams

Extraction Volume:

25.0 mL

Analyte

Result

Date Analyzed

Рb

360 250

ug/gram ug/gram 1/02/91 1/02/91

NEA ID: 90-S92

Client ID: TS 1127927-A

Sample Mass:

0.3682 grams

Extraction Volume:

25.0 mL

Analyte

Result

Date Analyzed

As Pb

520 240

ug/gram ug/gram 1/02/91 1/02/91

NEA ID: 90-S93

Client ID: TS 1127927-B

Sample Mass:

0.0095 grams

Extraction Volume: 25.0 mL

Analyte

290

ug/gram

Date Analyzed

Рb

150

ug/gram

1/02/91 1/02/91

NEA ID: 90-S94

As

·Client ID: TS 1127927-C

Sample Mass:

0.5393 grams

Result

Extraction Volume:

25.0 mL

Analyte

Result

Date Analyzed

As Pb 460 210 ug/gram ug/gram 1/02/91 1/02/91

NEA ID: 90-S95

Client ID: TS 1127927-D

Sample Mass:

0.4350 grams

Extraction Volume:

25.0 mL

Analyte

Result

Date Analyzed

As

690

ug/gram

1/02/91

ug/gram

1/02/91

Pb

290

Page: 12

Tacoma Slag Study 1/18/91 Client Name: Report Date: Date Received: Project Number: 316/001 Client ID: TS 1127930-A NEA ID: 90-S96 Sample Mass: 0.5040 grams Extraction Volume: 25.0 mL Analyte Result Date Analyzed 60 ug/gram 1/14/91 As Pb 69 ug/gram 1/14/91 NEA ID: 90-S97 Client ID: TS 1127930-B 0.5014 grams 25.0 mL Sample Mass: Extraction Volume: Analyte Result Date Analyzed 1/14/91 As ug/gram 65 1/14/91 Pb ug/gram NEA ID: 90-S98 Client ID: TS 1127930-C Sample Mass: 0.0821 grams Extraction Volume: 25.0 mL Result Analyte Date Analyzed 490 Pb ug/gram 1/14/91 67 1/14/91 As ug/gram NEA ID: 90-S99 Client ID: TS 1127930-D 0.2466 grams 26.0 mL Sample Mass: Extraction Volume: Analyte Result Date Analyzed Pb 180 ug/gram 1/14/91 As 71 ug/gram 1/14/91 NEA ID: 90-S100 Client ID: TS 1127931-A 0.4977 grams Extraction Volume: 25.0 mL Sample Mass: Result Date Analyzed Analyte -1/14/91 60 ug/gram As Pb 70 ug/gram 1/14/91

# Table A.1.

Page: 13

Client Name: Tacoma Slag Study Report Date: 1/18/91 Date Received: Project Number: 316/001 NEA ID: 90-S101 Client ID: TS 1127931-B 26.0 mL Sample Mass: 0.4957 grams Extraction Volume: Result Date Analyzed Analyte Pb 63 ug/gram 1/14/91 1/14/91 45 ug/gram As NEA ID: 90-S102 Client ID: TS 1127931-C 0.1766 grams Extraction Volume: 25.0 mL Sample Mass: Date Analyzed Analyte Result Pb 170 ug/gram 1/14/91 As 64 ug/gram 1/14/91 Client ID: TS 1127931-D NEA ID: 90-S103 Extraction Volume: 25.0 mL 0.2424 grams Sample Mass: Analyte Result . Date Analyzed 62 1/14/91 As ug/gram Pb 100 1/14/91 ug/gram NEA ID: 90-S104 Client ID: TS 1127932-A Sample Mass: 0.5154 grams Extraction Volume: 25.0 mL Analyte Result Date Analyzed 63 1/14/91 As ug/gram 87 Pb 1/14/91 ug/gram NEA ID: 90-S105 Client ID: TS 1127932-B Sample Mass: 0.5063 grams Extraction Volume: 25.0 mL Analyte Result Date Analyzed

1/14/91

1/14/91

49

48

ug/gram

ug/gram

Pb

As

Page: 14

Tacoma Slag Study Report Date: 1/18/91 Client Name: Date Received: Project Number: 316/001 NEA ID: 90-S106 Client ID: TS 1127932-C 0.4940 grams 25.0 mL Sample Mass: Extraction Volume: Result Date Analyzed Analyte Pb 1/14/91 150 ug/gram 1/14/91 As 43 ug/gram NEA ID: 90-S107 Client ID: TS 1127932-D Sample Mass: 0.5114 grams Extraction Volume: 25.0 mL Result Date Analyzed Analyte 100 1/14/91 Pb ug/gram 54 1/14/91 As ug/gram NEA ID: 90-S108 Client ID: TS 1127933-A 0.4930 grams Extraction Volume: 25.0 mL Sample Mass: Date Analyzed Analyte Result 1/21/91 As 61 ug/gram Pb 66 1/21/91 ug/gram NEA ID: 90-S109 Client ID: TS 1127933-B Sample Mass: 0.5108 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 39 ug/gram 1/14/91 Pb 42 ug/gram 1/14/91

NEA ID: 90-S110 Client ID: TS 1127933-C

Sample Mass: 0.4969 grams Extraction Volume: 25.0 mL

 Analyte
 Result
 Date Analyzed

 As
 47 ug/gram
 1/14/91

 Pb
 46 ug/gram
 1/14/91

Page: 15

Client Name: Tacoma Slag Study Report Date: 1/18/91 Date Received: Project Number: 316/001

NEA ID: 90-S111 Client ID: TS 1127933-D

Sample Mass: 0.4944 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 61 ug/gram 1/14/91 Pb 71 ug/gram 1/14/91

NEA ID: 90-S112 Client ID: TS 1127934-A

Sample Mass: 0.4994 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 50 ug/gram 1/14/91 Pb 55 ug/gram 1/14/91

NEA ID: 90-S113 Client ID: TS 1127934-B

Sample Mass: 0.5015 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 42 ug/gram 1/14/91 Pb 55 ug/gram 1/14/91

NEA ID: 90-S114 Client ID: TS 1127934-C

Sample Mass: 0.0191 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 81 ug/gram 1/14/91 Pb 630 ug/gram 1/14/91

NEA ID: 90-S115 Client ID: TS 1127934-D

Sample Mass: 0.1959 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

Pb 2300 ug/gram 1/14/91 As 680 ug/gram 1/14/91

Page: 16

Tacoma Slag Study Report Date: 1/18/91 Client Name: Date Received: Project Number: 316/001 NEA ID: 90-S126 Client ID: TS 1127939-A Extraction Volume: 25.0 mL 0.4960 grams Sample Mass: Result Date Analyzed Analyte 24 1/14/91 As ug/gram Pb 33 1/14/91 ug/gram NEA ID: 90-S127 Client ID: TS 1127939-B 0.4927 grams Sample Mass: Extraction Volume: 25.0 mL Analyte Result Date Analyzed Pb 86 1/14/91 ug/gram As 40 ug/gram 1/14/91 NEA ID: 90-S128 Client ID: TS 1127939-C 0.4941 grams Extraction Volume: 25.0 mL Sample Mass: Date Analyzed Analyte Result Рb 110 ug/gram 1/14/91 61 1/14/91 As ug/gram NEA ID: 90-S130 Client ID: TS 1127940 Sample Area: 2580.00 cm2 Extraction Volume: 25.0 mL Analyte Result Date Analyzed 1.5 ng/cm2 12/20/90 As 1.6 ng/cm2 12/31/90 Pb NEA ID: 90-S131 Client ID: TS 1127941-A 0.5398 grams Sample Mass: Extraction Volume: 25.0 mL Analyte Result Date Analyzed

300

160

ug/gram

ug/gram

As

Pb

1/02/91

1/02/91

Page:	17
-------	----

Client Name: Tacoma Slag Study Report Date: 1/18/91 Date Received: Project Number: 316/001

NEA ID: 90-S132 Client ID: TS 1127941-B

Sample Mass: 0.0036 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 580 ug/gram 1/02/91 Pb 500 ug/gram 1/02/91

NEA ID: 90-S133 Client ID: TS 1127941-C

Sample Mass: 0.4923 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 250 ug/gram 1/02/91 Pb 220 ug/gram 1/02/91

NEA ID: 90-S134 Client ID: TS 1127941-D

Sample Mass: 0.5049 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 300 ug/gram 1/02/91 Pb 280 ug/gram 1/02/91

NEA ID: 90-S135 Client ID: TS 1127942

Sample Area: 645 cm2 Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 580 ng/cm2 12/20/90

Pb 580 ng/cm2 12/31/90

NEA ID: 90-S136 Client ID: TS 1127943

Sample Mass: 0.2717 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 150 ug/gram 1/02/91 Pb 130 ug/gram 1/02/91

Page: 18

Client Name: Tacoma Slag Study Report Date: 1/18/91 Date Received: Project Number: 316/001

NEA ID: 90-S137 Client ID: TS 1127944

Sample Area: 645 cm2 Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 390 ng/cm2 12/20/90 Pb 360 ng/cm2 12/31/90

NEA ID: 90-S138 Client ID: TS 1127945

Sample Area: Wipe Blank Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As < 25 Total ng 12/20/90 Pb 420 Total ng 12/31/90

15 420 10tal ng 12/31/30

NEA ID: 90-S139 Client ID: TS 1127904-A

Sample Mass: 0.5026 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 50 ug/gram 1/14/91 Pb 85 ug/gram 1/14/91

NEA ID: 90-S144 Client ID: TS 1127904-B

Sample Mass: 0.4979 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 55 ug/gram 1/14/91 Pb 140 ug/gram 1/14/91

NEA ID: 90-S149 Client ID: TS 1127956/CM1

Sample Mass: 0.4952 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

As 240 ug/gram 1/02/91 Pb 27000 ug/gram 1/02/91

Page: 19

1/18/91

Tacoma Slag Study Report Date: Client Name:

Date Received: Project Number: 316/001

NEA ID: 90-S150 Client ID: TS 1127957/CM1

0.5106 Extraction Volume: 25.0 mL Sample Mass: grams

Result Date Analyzed Analyte

1/02/90 .83 ug/gram As

Pb 5.4 1/02/90 ug/gram

NEA ID: 90-S151 Client ID: TS 1127958

0.1380 grams Extraction Volume: 25.0 mL Sample Mass:

Result Date Analyzed Analyte

5400 ug/gram 1/02/91 As 83 Pb ug/gram 1/02/91

NEA ID: 90-S152 Client ID: TS 1127959

0.8261 grams Extraction Volume: 25.0 mL Sample Mass:

Analyte Result Date Analyzed

7000 1/02/91 As ug/gram Pb 23000 ug/gram 1/02/91

NEA ID: 90-S153 Client ID: TS 1127948-A

Sample Mass: 0.4537 grams Extraction Volume: 25.0 mL

Result Analyte Date Analyzed

240 1/02/90 ug/gram As

Pb 190 1/02/90 ug/gram

NEA ID: 90-S155 Client ID: TS 1127948-C

Sample Mass: 0.4528 grams Extraction Volume: 25.0 mL

Analyte Result Date Analyzed

1/02/91 180 ug/gram 230 Pb 1/02/91 ug/gram

20 Page:

Client Name:

Tacoma Slag Study

Report Date:

1/18/91

Date Received:

Project Number:

316/001

NEA ID: 90-S156

Client ID: TS 1127948-D

Sample Mass:

0.0292 grams

Extraction Volume: 25.0 mL

Analyte

Result

Date Analyzed

As РЪ 390 400 ug/gram ug/gram 1/02/91 1/02/91

NEA ID: 90-S158

Client ID: TS 1127943-B

Sample Mass:

0.0707 grams

Extraction Volume: 25.0 mL

Analyte

Result

Date Analyzed

As Pb

95 130 ug/gram ug/gram 1/02/91 1/02/91

NEA ID: 90-S159

Client ID: TS 1127943-C

Sample Mass:

0.2123 grams

Extraction Volume:

25.0 mL

Analyte

Result

Date Analyzed

As

NEA ID: 90-S160

190

ug/gram

1/02/91

Pb

270

ug/gram

1/02/91

Client ID: TS 1127943-D

Sample Mass:

0.0277 grams

Extraction Volume: 25.0 mL

Analyte

Result

Date Analyzed

As Рb

380 500 ug/gram ug/gram 1/02/91 1/02/91

Page: 1

Client Name: Tacoma Slag Study

Date Received:

Project Number: 316/001 Report Date: 1/18/91

NEA ID: 90-W132

Client ID: 1127905

Analyte Result Det. Limit Analysis Date

GFAA Ext V 50.0 mL

As 150 ug/L 7.5 ug total 1 ug/L 1/02/91 Pb 41 ug/L 20 ug total 2 ug/L 1/02/91

NEA ID: 90-W133 Client ID: 1127912

Analyte Result Det. Limit Analysis Date

GFAA Ext V 50.0 mL

As 1.0 ug/L .05 ug total 1 ug/L 1/02/91 Pb 2.7 ug/L .14 ug total 2 ug/L 1/02/91

NEA ID: 90-W134 Client ID: SPATULA RINSE

Analyte Result Det. Limit Analysis Date

GFAA Ext V 50.0 mL

As 7.6 ug/L .76 ug total 1 ug/L 1/02/91 Pb < 2 ug/L <.1 ug total 2 ug/L 1/02/91

NEA ID: 90-W135 Client ID: SOIL CORE SAMPLE RINSE

Analyte Result Det. Limit Analysis Date

GFAA Ext V 50.0 mL

As < 1 ug/L <.05 ug total 1 ug/L 1/02/91 Pb < 2 ug/L <.1 ug total 2 ug/L 1/02/91

NEA ID: 90-W136 Client ID: TS 1127928

Analyte Result Det. Limit Analysis Date

GFAA Ext V 50.0 mL

As 1200 ug/L 60 ug total 1 ug/L 1/02/91 Pb 700 ug/L 35 ug total 2 ug/L 1/02/91

Page:

Project Number: Client Name: Tacoma Slag Study 316/001

Report Date: 1/18/91 Date Received:

Client ID: TS 1127929 NEA ID: 90-W137

Result Det. Limit Analysis Date Analyte

GFAA Ext V 50.0 mL

2500 ug/L 120 ug total 1 ug/L 1000 ug/L 50 ug total 2 ug/L 1/02/91 1/02/91

Client ID: TS 1127937 NEA ID: 90-W138

Result Det. Limit Analysis Date Analyte

GFAA Ext V 50.0 mL

< 1 ug/L <.05 ug total 1 ug/L
2.0 ug/L .1 ug total 2 ug/L</pre> 1/02/91 1/02/91

NEA ID: 90-W139 Client ID: TS 1127938

Det. Limit Analysis Date Result Analyte

GFAA Ext V 50.0 mL

As 4.9 ug/L .24 ug total 1/02/91 1 ug/L 5.4 ug/L .27 ug total 1/02/91

2 ug/L

NEA ID: 90-W140 Client ID: TS 1127946

NEA ID: 90-W141 Client ID: TS 1127947

Det. Limit Result Analysis Date Analyte

GFAA Ext V 50.0 mL

900 ug/L 45 ug total 1 ug/L 760 ug/L 38 ug total 2 ug/L 1/02/91 1/02/91

Analyte Result Det. Limit Analysis Date

GFAA Ext V 50.0 mL

1100 ug/L 55 ug total 1 ug/L 1400 ug/L 70 ug total 2 ug/L 1100 ug/L 1/02/91 1/02/91 Pb

Page: 3

Client Name:

Tacoma Slag Study

Project Number: 316/001

Date Received:

Report Date:

1/18/91

NEA ID: 90-W142

Client ID: TS 1127949

Analyte

Result Det. Limit

Analysis Date

GFAA Ext V

50.0 mL

1 ug/L

1/02/91

510 ug/L 26 ug total 640 ug/L 32 ug total 2 ug/L

1/02/91

NEA ID: 90-W143

Client ID: TS 1127952

Analyte

Result

Det. Limit

Analysis Date

GFAA Ext V 310 mL

5.0 ug/L 1.6 ug total 4.0 ug/L 1.2 ug total

1 ug/L 2 ug/L 1/17/91 1/17/91

NEA ID: 90-W144 Client ID: TS 1127955

Analyte

PЪ

Result Det. Limit

Analysis Date

GFAA Ext V 280 mL

16 ug/L 4.5 ug total

1 ug/L

1/17/91

Pb

4.9 ug/L 1.4 ug total 2 ug/L

1/17/91

\_\_\_\_\_

Sample ID: 90-833

Client ID: TS 1127906-E

Exposed Area: 6.60 cm2

Deposit Mass: 877. +-

10. ug

Element	. ug/	cm2	:	ug/filt	cer		percent	
A1	2.426	- <b> </b>	0.3677	17.33 .		2.427	1.976	+- 0.2776
Si	16.79	- <b>j</b>	2.223	110.8	. <del>j.</del> <u>.</u>	L4.67	12.64	+- 1.679
E.	0.0000	<del> .</del>	0.0084	0.0000	- <del> </del>	0.0554	0.0000	+- 0.0063
S	0.0000	+	0.2119	0.000	··j·· ····	1.399	0.000	+- 0.1595
Cl	0.0000		0.0302	0.0000		0.1993	0.0000	+- 0.0227
K	0.5155	· <del> </del>	0.0584	3.402	4	0.3854	0.3879	+- 0.0442
Ca	3.015	+	0.3374	19.90	-j	2.227	2.269	+- 0.2552
Τi	0.3539		0.0183	2.336		0.1208	0.2463	+- 0.0141
V .	0.0000	+	0.0045	0.0000	-	0.0297	0.0000	+- 0.0034
Cr	0.0938		0.0054	0.6191		0.0356	0.0706	+- 0.0041
Mr)	0.0000		0.0033	0.000	- <del>}-</del>	0.0218	0.0000	+- 0.0025
Fe	22.47		1.113	148.3	<del></del>	7.346	16.91	<b></b> 0.8595
Ni	0.0000		0.0033	0.000	-	0.0218	0.0000	+- 0.0025
Cu	2.433		0.1236	14.06		0.8158	1.831	+- 0.0953
Zn	0.8015		0.0413	5.290	· <del>-</del>	0.2726	0.6032	+- 0.0318
Ga	0.0000		0.0035	0.000		0.0231	0.0000	+- 0.0026
Ge	0.0000			0.000	-	0.0119	0.0000	+- 0.0014
As	2.272		0.1297	15.00	-+		1.710	+- 0.0995
Se	0.0000			0.000		0.0132	0.0000	+- 0.0015
Br	0.000			0.000		0.0568	0.0000	+- 0.0065
Rb	0.0000					0.0125	•	+- 0.0014
Sr	0.0154			0.1016			0.0116	+- 0.0015
Y	0.0000					0.0152	0.0000	+- 0.0017
Zr	0.0000			0.0000			0.0000	+- 0.0032
Мо	0.1855			1.224		0.0700	0.1396	+- 0.0081
Pd	0.0036		*	0.0238		0.1096	0.0027	+- 0.0125
Ag	0.0000			0.0000		0.1280	0.0000	+- 0.0146
Cd	0.0414			0.2732		0.1399	0.0312	+- 0.0160
In	0.0000			0.0000		0.1412	0.0000	+- 0.0161
Sn	0.0653			0.4310			0.0491	+- 0.0178
Sb	0.4552			3.004		0.2409	0.3426	+- 0.0277
Ba	0.0000			0.0000		0.5518	0.0000	+- 0.0629
La	0.1476		0.1133	0.9742		0.7478	0.1111	+- 0.0853
Hg	0.0000	,				0.0238	0.0000	+- 0.0027
Pb	1.322	- <del> </del>	0.0669	8.725	+	0.4415	0.9949	+- 0.0516

Sample ID: 91-820

Client ID: TS 1127950-1-E

Exposed Area: 6.60 cm2

Deposit Mass: 784. +-

4. +- 10. ug

Element -ug/cm2 uq/filter percent A11.827 +- 0.2628 12.06 +- 1.734 1.538 +-0.2221 $\Im i$ 14.19 +- 1.878 93.65 +-12.39 11.95 +- 1.588 100 ·0.0000 +~ 0.0075 0.0000 +- 0.0495 0.0000 +- 0.0063 9 0.0000 +- 0.1837 0.0000 +- 1.212 0.0000 +- 0.1546 C10.0000 +- 0.0270 0.0000 +- 0.1782 0.0000 +- 0.0227 0.3043 0.3615 +- 0.04132.386 +- 0.0350 k. +- 0.2726 Ca 3.123 +-0.349520.61 +- 2.307 2.629 +- 0.2961 0.2963 +- 0.01551.956 +- 0.1023 0.2494 +- 0.0134 Τi +- 0.0034  $\vee$ 0.0000 +- 0.00400.0000 +- 0.02640.0000 0.0418 +- 0.00320.2759 +- 0.02110.0352 +- 0.0027 CrMn 0.0000 + - 0.00310.0000 +- 0.0205 0.0000 +- 0.0024 ĨF@ 23.24 153.4 +- 7.597 19.56 +- 1.001 +- 1.151 0.0000 +- 0.0032 0.0000 +- 0.02110.0000 +- 0.0027 Ni 2.222 +- 0.0980 Cu +- 0.1129 14.67 +- 0.7451 1.871 1.662 +- 0.0851 10.97 +- 0.5617 1.399 +- 0.0738 Zη +- 0.0031 0.0000 +- 0.0037 0.0000 +- 0.0244 0.0000 Ga 0.0000 + - 0.00210.0000 +- 0.01390.0000 +- 0.0018 Ge 5.483 +- 0.2767 36.19 +- 1.826 +- 0.2403 As 4.616 Se 0.0000 +- 0.00260.0000 +- 0.01720.0000 +- 0.0022 0.0000 +- 0.0196 0.0000 +- 0.1294+- 0.0165  $\mathbf{B}r$ 0.0000 Rb 0.0000 +- 0.0029 0.0000 +- 0.0191. 0.0000 +- 0.0024 0.0053 +- 0.0019 0.0350 +- 0.0125 Sr0.0045 +- 0.0016 γ 0.0000 +- 0.0023 0.0000 +- 0.0152 0.0000 +- 0.0019 Ζr 0.0000 +-- 0.0045 0.0000 + 0.02970.0000 +- 0.0038 0.2079 +- 0.0121 0.1750 ΜO 1.372 +- 0.0799 +- 0.0104 Pd 0.0364 +- 0.0182 0.2402 +- 0.12010.0306 +- 0.0153 0.0352 +- 0.0201 0.2323 +- 0.13270.0296 +- 0.0169 Αq 0.0434 +- 0.0217 0.2864 +- 0.14320.0365 Cd +- 0.0183  $I \cap$ 0.0000 +- 0.02190.0000 + - 0.14450.0000 +- 0.0184 0.0439 +- 0.0240 0.2897 +- 0.1584 0.0370 +- 0.0202 Sn 0.6575 +- 0.0448 +- 0.2957 Sb 4.340 0.5535 +- 0.0384 0.0009 +- 0.07730.0059 +- 0.51020.0008 +- 0.0651 Вa 0.0000 +- 0.10710.0000 +- 0.7069 L.a 0.0000 +-0.0902Ha 0.0000 +- 0.00430.0000 +- 0.0284 0,0000 +- 0.0036 Fb 1.380 +- 0.0698 9.108 +- 0.4607 1.162 +- 0.0606 316/001

Table A.1

Sample ID: 91-S21

Ва

L.ē

Hq

Fb

Client ID: TS 1127953-4-E

Exposed Area: 6.60 cm2

0.0124 +- 0.0800

0.0000 +~ 0.1090

0.0000 +- 0.0038

+- 0.0715

1.414

843, +--10. ua

Deposit Mass: Element uq/cm2 ug/filter percent AI4.231 +- 0.5834 27.92 +- 3.850 3.313 +- 0.4584 Si. 23.22 +- 3.073 153.3 +-20.28 18.18 +- 2.416 .... 0.0000 +- 0.0090 0.0000 +- 0.0594 0.0000 +- 0.0070 S 0.0000 +- 0.2214 0.00000 + - 1.4610.0000 +- 0.1733 C10.0000 +- 0.0317 0.0000 +- 0.2092 0.0000 +- 0.0248 0.5989 +- 0.0678 3.953 K +- 0.4475 0.4689 +- 0.0534 +- 0.4480 26.43 Ca 4.004 +- 2.957 3.135 +- 0.3527 Тi 0.3873 + - 0.02002.556 +- 0.1320 0.3032 +- 0.0161 V 0.0000 +- 0.0048 0.0000 +- 0.03170.0000 +- 0.0038 Cr 0.0538 +- 0.0038 0.3551 +- 0.02510.0421 +- 0.0030 Mn 0.0000 +- 0.0034 0.0000 +- 0.0224 0.0000 +- 0.0027 Fe 24.76 +- 1.227 163.4 +- 8.098 19.39 +- 0.9878 Ni 0.0000 +- 0.0031 0.0000 +- 0.02050.0000 +- 0.0024 Cu 1.725 +- 0.0878 11.38 +- 0.5795 1.351 +- 0.0706 +- 0.0553  $Zr_1$ 1.078 7.115 +- 0.3650 0.8440 +- 0.0444 Θæ 0.0000 +- 0.0034 0.0000 +- 0.0224 0.0000 +- 0.0027 0.0000 +- 0.0125 Ge 0.0000 +~ 0.0019 0.0000 +- 0.0015 As 2.114 +- 0.1258 13.95 +- 0.8303 1.655 +- 0.1004 Se 0.0000 +- 0.00190.0000 +- 0.0125 0.0000 +- 0.0015 Br 0.0000 +~ 0.0082 0.0000 +- 0.05410.000 +- 0.0064 Rb 0.0000 + 0.00190.0000 +- 0.0125. 0.0000 +- 0.0015 Sr 0.0169 +- 0.0020 0.1115 + - 0.01320.0132 +- 0.0016 +- 0.0018 Υ 0.0000 +- 0.0023 0.0000 +- 0.0152 0.0000 Zr. 0.0000 +- 0.0044 0.0000 +- 0.02900.0000 +- 0.0034 Mo 0.1381 +- 0.0085 0.9115 +- 0.05610.1081 +- 0.0068 Pd 0.0117 + 0.01620.0772 +- 0.10690.0092 +- 0.0127 0,0000 +- 0.0189 0.00000 +- 0.1247Αq 0.0000 +- 0.0148 0.0416 +- 0.0208 0.2746 + - 0.13730.0326 Cd +- 0.0163 In 0.0000 +- 0.02040.00000 +- 0.13460.0000 +- 0.0160 Sn 0.0903 +- 0.02290.5960 +- 0.1511 0.0707 +- 0.0179 Sb 3.774 +- 0.2653 +- 0.0319 0.5718 +- 0.04020.4477

0.0818 +- 0.5280

0.0000 +- 0.7194

0.0000 +- 0.0251

+- 0.4719

9.332

0.0097

0.0000

1.107

0.0000

+- 0.0626

+- 0.0853

+- 0.0030

+- 0.0575

Sample ID: 91-822

Client ID: TS 1127926-E

Exposed Area: 6.60 cm2

Deposit Mass: 756. +-

10. ug

Element	ug/cm2		ug/fil	ug/filter			percent		
ΑI	2.255	- <b> </b>	0.3157	14.88	44	2.084	1.969	- <b> </b>	0.2768
Si	14.45		1.913	95.37		12.63	12.62	-j	1.678
p	0.0000	·· <del> </del> ··	0.0076	0.0000	- <del>i</del>	0.0502	0.0000		0.0066
9	0.0000	-}	0.1593	0.0000	[	1.051	0.0000	- <b>j</b>	0.1391
Cl	0.0000	- <del> </del>	0.0244	0.0000	-1	0.1610	0.0000	· ·	0.0213
K	0.4795	-j	0.0544	3.165	+	0.3590	0.4186	- <del> -</del>	0.0478
Ca	2.840	+	0.3179	18.74	- <del> -</del>	2.098	2,479	· <del>†</del>	0.2795
Ti	0.3190		0.0166	2.105	+	0.1096	0.2785	+	0.0150
V	0.0000	<del>-}</del>	0.0041	0.0000	+	0.0271	0.0000	· <b>+</b>	0.0036
Cr	0.0742		0.0045	0.4897	+	0.0297	0.0648	+	0.0040
Min	0.0000	+	0.0030	0.0000	÷	0.0198	0.0000	+	0.0026
Fe	19.62	-	0.9721	129.5		6.416	17.13	4	0.8784
Ni			0.0034	0,0000		0.0224	0,.0000		0.0030
Cu	2.043		0.1039	13,48		0.6857	1.784		0.0937
Zn			0.0360	4.597		0.2376	0.6081		0.0324
Ga	0.0000	<b></b> .	0.0032	.0.000			0.0000		0.0028
Ge			0.0020			0.0132	0.0000		0.0017
As	1.811		0.1031	11.95		0.6805	1.581		0.0924
Se			0.0020	0.0000			0.0000		0.0017
Br			0.0070			0.0462			0.0061
Rb			0.0019			0.0125	. 0.0000		0.0017
Sr			0.0019			0.0125	0.0088		0.0017
, Y			0.0023			0.0152	0.0000		0.0020
Zr			0.0037			0.0244	0.0000		0.0032
Мо			0.0093	1.081		0.0614	0.1430		0.0083
Pd			0.0153			0.1010	0.0000		0.0134
Ag			0.0178			0.1175	0.0000		0.0155
Cd			0.0194			0.1280	0.0038		0.0169
In			0.0196			0.1294	0.0000		0.0171
Sn			0.0217			0.1432	0.0104		0.0189
Sb			0.0316	2.305		0.2086	0.3049		0.0279
Ba			0.0784	0.7570		0.5174	0.1001		0.0485
La			0.1062	1.037		0.7009	0.1372		0.0927
Hg			0.0041	0.0000		0.0271	0.0000		0.0036
Pb	1.038	- <del>†</del>	0.0527	6.851	- <del> </del>	0.3478	0.9062	j	0.0475

Exposed Area: 6.60 cm2 Deposit Mass. Deposit Mass: 938. +-

Element	ug/cm2	ug/filter	percent ·		
A1	2.168 +- 0.2940	14.31 +- 1.940	1.525 +- 0.2075		
Si	7.803 +- 1.033	51.50 +- 6.818	5.490 +- 0.7292		
E.	0.0780 +- 0.0204	0.5148 +- 0.1346	0.0549 +- 0.0144		
S	3.090 +- 0.3482	20.39 +- 2.298	2.174 +- 0.2461		
C1 .	0.3491 +- 0.0489	2.304 +- 0.3227	0.2456 +- 0.0345		
K	3.584 +- 0.4014	23.65 +- 2.649	2.522 +- 0.2837		
Ca .	13.23 +- 1.479	87.32 <i>+-</i> 9.761	9.309 +- 1.045		
Τi.	0.4616 +- 0.0236	3.047 +- 0.1558	0.3248 +- 0.0170		
V	0.0099 +- 0.0053	0.0453 +- 0.0350	0.0070 +- 0.0037		
Cr	0.0336 +- 0.0026	0.2218 +- 0.0172	0.0236 +- 0.0018		
Mn	0.1636 +- 0.0085	1.080 +- 0.0561	0.1151 +- 0.0061		
Fe	2.570 +- 0.1279	16.96 +- 0.8441	1.808 +- 0.0920		
Ni	0.0081 +- 0.0015	0.0535 +- 0.0099	0.0057 +- 0.0011		
Cu	0.0805 +- 0.0045	0.5313 +- 0.0297	0.0566 +- 0.0032		
Zn	0.2563 +- 0.0134	1.692 +- 0.0884	0.1803 +- 0.0096		
Ga	0.0000 +- 0.0012	0.0000 +- 0.0079	0.0000 +- 0.0008		
Ge	0.0000 +- 0.0008	0.0000 +- 0.0053	0.0000 +- 0.0006		
As	0.0476 +- 0.0050	0.3142 +- 0.0330	0.0335 +- 0.0035		
Se	0.0000 +- 0.0008	0.0000 +- 0.0053	0.0000 +- 0.0006		
Br	0.0256 +- 0.0018	0.1690 + 0.0119	0.0180 +- 0.0013		
Rb	0.0038 +- 0.0013	0.0251 +- 0.0086	0.0027 +- 0.0009		
Sr	0.0745 +- 0.0041	0.4917 +- 0.0271	0.0524 +- 0.0029		
Υ	0.0000 +- 0.0017	0.0000 +- 0.0112	0.0000 +- 0.0012		
Zr	0.0296 +- 0.0032	0.1954 +- 0.0211	0.0208 +- 0.0023		
Mo	0.0036 +- 0.0029	0.0238 +- 0.0191	0.0025 +- 0.0020		
۴d	0.0000 +- 0.0088	0.0000 +- 0.0581	0.0000 +- 0.0062		
Ag	0.0044 +- 0.0106	0.0290 +- 0.0700	0.0031 +- 0.0075		
Cq	0.0137 +- 0.0118	0.0904 +- 0.0779	0.0096 +- 0.0083		
Ιn	0.0000 +- 0.0136	0.0000 + 0.0898	0.0000 +- 0.0096		
Sn	0.0000 +- 0.0167	0.0000 +- 0.1102	0.0000 +- 0.0118		
Sb	0.0000 +- 0.0203	0.0000 +- 0.1340	0.0000 +- 0.0143		
Ba	0.2311 +- 0.0791	1.525 +- 0.5221	0.1626 +- 0.0557		
La	0.1893 +- 0.1052	1.249 +- 0.6943	0.1332 +- 0.0740		
Hg	0.0000 +- 0.0017	0.0000 +- 0.0112	0.0000 +- 0.0012		
F'b	0.0720 +- 0.0051	0.4752 +- 0.0337	0.0507 +- 0.0036		

316/001

Table A.1

Exposed Area: 6.60 cm2

Sample ID: 91-S19 Client ID: TS 1127939-E

Deposit Mass: 589. +-10. ug

Element	ug/	cmI	•	ug/filt	ie r		percent	
ĄΙ	1.317		0.1828	8.692		1.206	1.476	+- 0.2064
Si	7.465	- <del> </del>	0.9882	49.27	·	6.522	8.365	+- 1.116
<b>;</b> :-	0.0000	<del></del>	0.0066	0.000		0.0436	0.0000	+- 0.0074
3	0.8970	- <del>[</del>	0.1035	5.920		0.6831	1.005	+- 0.1172
Cl ·	0.5247	- <b>ļ</b> -	0.0611	3.463	-	0.4033	0.5879	+- 0.0692
K	0.7782 -	· <del> </del>	0.0876	5.136	+	0.5782	0.8720	+- 0.0993
Ca	4.162	<b>⊹</b> ∵	0.4657	27.47	<b>j</b>	3.074	4.664	+- 0.5278
Ti	0.3172 -	<del></del>	0.0163	2,094	<del>-j.</del>	0.1076	0.3554	+- 0.0192
V	0.0031	- <b> </b>	0.0036	0.0205	<b> </b>	0.0238	0.0035	+- O.0040
Cr	0.0241	<del>- </del>	0.0018	0.1591	-	0.0119	0.0270	+- 0.0021
Mn	0.0240	· <del>i</del> ·····	0.0019	0.1584	- <del> </del>	0.0125	0.0269	+- 0.0022
Fe	1.455	- <b> </b>	0.0727	9.603	<del> -</del>	0.4798	1.630	+- 0.0860
Ni	0.0024	· <del> </del>	0.0012	0.0172		0.0079	0.0029	+- 0.0013
Cu	0.0619	+	0.0036	0.4085		0.0238	0.0694	+- 0.0042
Zn	0.1107	- <del>j-</del>	0.0060	0.7306		0.0396	0.1240	+- 0.0070
Ga	0.0000		0.0009	0,0000	+	0.0059	0.0000	+- 0.0010
Ge	0.0007 -	-	0.0007	0.0046		0.0046	0.0008	4- 0.0008
As	0.0148	- <del> </del> -	0.0025	0.0977	- <del> </del>	0.0165	0.0166	+- 0.0028
Se			0.0007	0.0000		0.0046	0.0000	0.0008
Br			0.0009	0.0238	··•	0.0059	0.0040	+- 0,0010
Rb	0.0003	- <b> -</b> ·	0.0011	0.0020	-j	0.0073.	0.0003	+- 0.0012
Sr		- <del> </del>	0.0015	0.0838		0.0099	0.0142	4- 0.0017
Υ			0.0017	0.0000		0.0112	0.0000	+- 0.0019
Z r-	0.1554	··[	0.0084	1.026		0.0554	0.1741	+- 0.0099
Mo			0.0030	0.0119	<del>-j</del>	0.0198.	0.0020	<del>+-</del> 0.0034
Pd		<del> </del> -		0.0000			0.0000	+- 0.0082
Аg		·+·	0.0093	0.1076		0.0614	0.0183	+- 0.0104
Cq		}		0.1439		0.0719	0.0244	+- 0.0122
Ιn		÷		0.0000	- <del>-</del> j		0.0000	+- 0.0143
Sn				0.1010	· <del> </del> ··		0.0171	+- 0.0178
Sb				0.3392			0.0576	+- 0.0223
Ba			0.0765	0.1934	- <del> </del>		0.0328	+- 0.0857
La				0.2277	- <del> </del>		0.0387	+- 0.1188
Hg		· <del> -</del>	0.0014	0.000	-j		0.0000	+- 0.0016
₽-b	0.0285	·· <b>j-</b>	0.0035	0.1881		0.0231	0.0319	+- 0.0040

# REPLICATE REPORT 316/01 PROTOCOL: 4 SA

TROTOCOE. . 4 5

SAMPLE ID: TS1127953-4D

PARTICLE SIZE: C
ORIGINAL ID: S0021
REPLICATE ID: 00021

EXPOSED AREA: 6.60 SOUARE CM

MASS OF DEPOSIT: 0.+- 0. MICROGRAMS

ELEMENT	ORIGI UG/C		REPLI UG/C		CHANGE UG/C		PERCE ERRO	
AL	4.3120+-	.5946	4.2657+-	.5883	0463+-	.8364	-1.1+-	19.4
SI	23.5355+-	3.1148	23.3224+-	3.0866	2131+-4	.3851	9+-	18.6
P	-+0000+-	.0092	.0000+-	.0092	-+0000+-	.0130		
S	.0000+-	. 2224	.0000+-	.2188	.0000+-	.3120		
$C\Gamma$	.0000+-	.0319	.0000+-	.0310	.0000+-	.0445		
K	.6000+-	.0679	.6204+-	.0702	.0204+-	.0977	3.4+-	16.3
CA	4.0089+-	. 4486	4.0410+-	.4522	.0321+-	.6370	.8+-	15.9
ΤI	.3873+-	.0200	.3943+-	.0203	.0070+-	.0285	1.8+-	7.4
V	.0000+-	.0048	.0000+-	.0049	.0000+-	.0069		
CR	.0538+-	.0038	.0596+-	.0040	.0058+-	.0055	10.8+-	10.3
MN	.0000+-	.0034	-0000+-	.0034	.0000+-	.0048		
FE	24.7643+-	1.2266	24.7223+-	1.2245	0420+-1		2+-	7.0
NI	.0000+-	.0031	.0000+-	.0031		.0044		
CU	1.7248+-	.0878	1.7201+-	.0875	0047+-	.1240	3+-	7.2
ZN	1.0775+-	.0553	1.0799+-	.0555	.0024+-	.0783	. 2+-	7.3
GA	.0000+-	.0034	.0000+		.0000+-	.0048		
GE	.0000+-	.0019	.0000+-	.0019	.0000+-	.0027		
ÀS	2.1140+-	.1258	2.1235+-	.1265	.0095+-	.1784	. 4+-	8.4
SE	-+0000+-	.0019	-0000+-	.0020	-+0000+-	.0028		
BR	.0000+-	.0082	.0000+-	.0082	.0000+-	.0116		
RB	.0000+-	.0019	.0000+-	.0019	.0000+-	.0027		
SR	.0169+-	.0020	.0166+-	.0020	0003+-	.0028	-1.8+-	16.7
Y	.0000+-	.0023	.0000+-	.0023	.0000+-	.0033		
ZR	.0000+-	.0044	.0000+-	.0044	.0000+-	.0062		
MO	.1381+-	.0085	.1450+-	.0090	.0069+-	.0124	5.0+-	9.0
PD	.0117+-	.0162	.0256+-	.0164	.0139+-	.0231		
AG	.0000+-	.0189	.0000+-	.0189	-+0000+-	.0267	v	
CD	.0416+-	.0208	.0398+-	.0205	0018+-	.0292		
IN	.0000+-	.0204	.0000+-	.0204	-+0000+-	.0288		
SN	.0903+-	.0229	.0797+~	.0229	0106+-	.0324	-11.7+-	35.9
SB	.5718+-	.0402	. 4768+-	.0365	0950+-	.0543	-16.6+-	9.5
BA	.0124+-	.0800	.0000+~	.0791	0124+-	.1125		
LA	-+0000+-	.1090	.0560+-	.1084	.0560+-	.1537		
HG	.0000+-	.0038	.0000+~	.0038	.0000+-	.0054	_	
PB	1.4144+-	.0715	1.4238+-	.0720	.0094+-	.1015	.7+-	7.2

# QUALITY ASSURANCE REPORT

GFAA

SAMPLE RANGE: 90-W(143,144)

SAMPLE DESCRIPTION: Water samples

# **DUPLICATE ANALYSIS**

DATE	ANALYSIS ID	ANALYTES	SAMPLE (ug/L)	DUPLICATE (ug/L)	RPD
1/17/91	90-W144	As Pb	16.5 4.9	16.3 4.9	1.2

# PRE-DIGESTION SPIKE ANALYSIS

DATE	ANALYSIS ID	ANALYTES	SPIKE AMOUNT (ug/L)	SPIKE REC. (ug/L)	SPIKE % RECOVERY
1/17/91	90-W143 S <sub>1</sub>	As Pb	20.0	19.4 10.7	97.0 107
	90-W143 S <sub>2</sub>	As Pb	20.0 10.0	20.4 10.4	102 104

# POST-DIGESTION SPIKE ANALYSIS

DATE	ANALYSIS ID	ANALYTES	SPIKE AMOUNT (ug/L)	SPIKE REC. (ug/L)	SPIKE % RECOVERY
1/17/91	90-W143	As Pb	12.5 5.0	12.6 4.8	101 96

RPD: Relative Percent Difference  $[(X_1-X_2)/[(X_1+X_2)/2]*100$ 

SPIKE % RECOVERY:

[(sample+spike - unspiked sample)/spike added]\*100

# QUALITY ASSURANCE REPORT

# **GFAA**

SAMPLE RANGE: 90-W132 thru 90-W142

SAMPLE DESCRIPTION: Water and acetone/pentane rinses

# **DUPLICATE ANALYSIS**

DATE	ANALYSIS ID	ANALYTES	SAMPLE (ug/L)	DUPLICATE (ug/L)	RPD
12/21/90	90-W137 90-W141	As	2490 1060	2470 1120	0.8 5.5
12/27/90 1/02/91	90-W139 90-W137	Pb	5.43 1031	5.39 1073	0.7 4.0

# POST-DIGESTION SPIKE ANALYSIS

DATE	ANALYSIS ID	ANALYTES	SPIKE AMOUNT (ug/L)	SPIKE REC. (ug/L)	SPIKE % RECOVERY
12/21/90	90-W136 90-W141	As	12.5 12.5	10.2 11.4	81.6 91.2
12/27/90 1/02/90	90-W141 90-W137	Pb	10.0 25.0	8.80 26.5	88.0 106

RPD: Relative Percent Difference  $[(X_1-X_2)/[(X_1+X_2)/2]*100$ 

SPIKE % RECOVERY:

[(sample+spike - unspiked sample)/spike added]\*100

APPROVED	BY:	Q	cS	 DATE:	_ 1/2	H91	
•	•		_			1	

# QUALITY ASSURANCE REPORT

# **GFAA**

SAMPLE RANGE: 90-S(22,23,80-83,130,135,137,138)

SAMPLE DESCRIPTION: Wipe Samples

# DUPLICATE ANALYSIS

DATE	ANALYSIS ID	ANALYTES	SAMPLE (ug/L)	DUPLICATE (ug/L)	RPD
12/20/90	90-S81 90-S137	As	77.6 10500	73.4 10100	5.6 3.9
12/31/90	90-S130 90-S138	Pb	170 16.6	172 16.9	1.2
01/03/91	90 <b>-</b> S83	Pb	174	172	1.2

# POST-DIGESTION SPIKE ANALYSIS

DATE	ANALYSIS ID	ANALYTES	SPIKE AMOUNT (ug/L)	SPIKE REC. (ug/L)	SPIKE % RECOVERY
12/20/90	90-S23 90-S137	As	12.5 12.5	11.1	88.8 91.2
12/31/90	90-S80	Pb	25.0	23.0	92.0
01/03/90	90 <b>-</b> S83	Pb	25.0	27.9	112

RPD: Relative Percent Difference  $[(X_1-X_2)/[(X_1+X_2)/2]*100$ 

SPIKE % RECOVERY:

[(sample+spike - unspiked sample)/spike added]\*100

APPROVED BY: D	DATE:	1/24/91
----------------	-------	---------

# QUALITY ASSURANCE REPORT

# GFAA and ICAP

SAMPLE RANGE: 90-S(24-27,88-95,131-136,149-153,155-156,158-160) SAMPLE DESCRIPTION: Soil Samples

# DUPLICATE ANALYSIS

DATE & INSTRUMENT	ANALYSIS ID	ANALYTES	SAMPLE (ug/ml)	(ug/ml)	RPD
12/27/90 ICAP	90-S26 90-S91 90-S131	Pb Pb As Pb As	1.75 5.20 7.50 3.42 6.54	1.84 5.09 7.64 3.59 6.28	5.0 2.1 1.8 4.8 4.1
12/28/90 ICAP	90-S149 90-S152	Pb Pb As	502 754 227	478 765 221	4.9 1.4 2.7
12/28/90 GFAA	90-S158	Pb	.382	.381	0.3
12/31/90 GFAA	90 <b>-</b> S156	Pb	.471	.461	2.1
01/02/91 GFAA	90-S25 90-S132 90-S156	As As As	.275 .083 .458	.284 .082 .452	3.2 1.2 1.3

RPD: Relative Percent Difference  $[(X_1-X_2)/[(X_1+X_2)/2]*100$ 

APPROVED BY:  $\frac{124/91}{}$ 

# QUALITY ASSURANCE REPORT

# GFAA and ICAP

SAMPLE RANGE: 90-S(24-27,88-95,131-136,149-153,155-156,158-160) SAMPLE DESCRIPTION: Soil Samples

# POST-DIGESTION SPIKE ANALYSIS

DATE & INSTRUMENT	ANALYSIS ID	ANALYTES	SPIKE AMOUNT (ug/ml)	SPIKE REC. (ug/ml)	SPIKE % RECOVERY
12/28/90 ICAP	90 <b>-</b> S24	Pb As	2.5 2.5	2.67 2.53	107 101
·	90 <b>-</b> S95	Pb As	2.5	2.50 2.57	100 103
	90 <b>-</b> S89	Pb As	2.5 2.5	2.60 2.37	104 94.8
12/28/90 GFAA	90 <b>-</b> S156	Pb	.025	.0248	99.2
01/02/91 GFAA	90 <b>-</b> S25	As	.025	.0214	85.6

# QUALITY ASSURANCE REPORT

# GFAA and ICAP

SAMPLE RANGE: 90-S(34-37,39-42,44-47,49-52,54-57,58-61) SAMPLE DESCRIPTION: Soil Samples

# **DUPLICATE ANALYSIS**

DATE & INSTRUMENT	ANALYSIS ID	ANALYTES	SAMPLE (ug/ml)	DUPLICATE (ug/ml)	RPD
01/04/91 ICAP	90 <b>-</b> S35	Pb As	2.05 1.22	2.00 1.31	2.5 7.1
ICAF	90-S40	Pb	4.59	4.58	0.2
		As	2.56	2.53	1.2
	90-S49	Pb	8.25	8.34	1.1
		As	2.42	2.38	1.7
01/09/91	90 <b>-</b> S50	Pb	•555	.551	0.7
GFAA	90 <b>-</b> S60	Pb	.758	.758	0.0
	90 <b>-</b> S57	As	.630	.623	1.1
	90 <b>-</b> S60	As	.324	.313	3.4

ANALYSIS ID	ANALYTES	SPIKE (ug/ml)	SPIKE REC. (ug/ml)	SPIKE % RECOVERY
90-S35 S	Pb	2.0	2.13	106
	As	4.0	4.05	101
90-S44 S.	Pb	2.0	2.02	101
•	As	4.0	4.12	103
90-S44 S <sub>2</sub>	Pb	2.0	1.99	99.5
2	As	4.0	4.01	100
90-S46 S.	P.b	2.0	1.63	81.5
•	As	4.0	3.75	93.8
90-S46 S <sub>2</sub>	Pb	2.0	1.80	90.0
2	As	4.0	3.64	91.0

RPD: Relative Percent Difference  $[(X_1-X_2)/[(X_1+X_2)/2]*100$ 

SPIKE % RECOVERY:

[(sample+spike - unspiked sample)/spike added]\*100

APPROVED	BY:	905	<u></u>	DATE:		124/91	
					7		

# QUALITY ASSURANCE REPORT

# GFAA and ICAP

SAMPLE RANGE: 90-S(34-37,39-42,44-47,49-52,54-57,58-61)

SAMPLE DESCRIPTION: Soil Samples

# POST-DIGESTION SPIKE ANALYSIS

DATE & INSTRUMENT	ANALYSIS ID	ANALYTES	SPIKE AMOUNT (ug/ml)	SPIKE REC. (ug/ml)	SPIKE % RECOVERY
01/04/91	90 <b>-</b> S39	Pb	2.5	2.72	109
ICAP		As	2.5	2.88	115
	90-S41	Pb	2.5 .	2.70	108
		As	2.5	2.87	115
01/09/91	90 <b>-</b> S44	Pb	.025	.0232	92.8
GFAA		As	.025	.0228	91.2

SPIKE % RECOVERY:

[(sample+spike - unspiked sample)/spike added]\*100

APPROVED BY:	<u> 9c5</u>	DATE:		124/91	
			,		

# QUALITY, ASSURANCE REPORT

# GFAA and ICAP

SAMPLE RANGE: 90-S(62-69,84-87,96-115,126-128,139,144) 91-S(1-17)

SAMPLE DESCRIPTION: Soil Samples

# DUPLICATE ANALYSIS

DATE & INSTRUMENT	ANALYSIS ID	ANALYTES	SAMPLE (ug/ml)	DUPLICATE (ug/ml)	RPD
01/11/91	90 <b>-</b> S64	As	.448	.452	0.9
GFAA	90-S85 90-S100	As As	1.34 1.30	1.36 1.32	1.5 1.5
•			•		
01/13/91	90 <b>-</b> S84	Pb	1.60	1.76	9.5
ICAP		As	1.51	1.57	3.9
	90 <b>-</b> S99	Pb	1.65	1.62	1.8
	90 <b>-</b> S108	Pb	1.27	1.27	0.0
		As	1.19	1.30	8.8
	91 <b>-</b> S01	Pb	3.46	3.35	3.2
		As	1.43	1.45	1.4
01/14/91	90-S105	As	.969	.969	0.0
GFAA	90-S115	As	.531	.496	6.8
••	90-S64	Pb	.848	.840	0.9
	90 <b>-</b> S110	Pb	.922	.935	1.4
01/14/91	91 <b>-</b> S13	Pb	54.3	53.6	1.3
ICAP		As	83.1	83.4	0.4
	91 <b>-</b> S17	Pb	90.6	91.4	0.9
		As	137	136	0.7

RPD: Relative Percent Difference  $[(X_1-X_2)/[(X_1+X_2)/2]*100]$ 

APPROVED BY: DATE:

# QUALITY ASSURANCE REPORT

# GFAA and ICAP

SAMPLE RANGE: 90-S(62-69,84-87,96-115,126-128,139,144)

91-S(1-17)

SAMPLE DESCRIPTION: Soil Samples

# PRE-DIGESTION SPIKE ANALYSIS : ICAP

DATE	ANALYSIS ID	ANALYTES	SPIKE AMOUNT (ug/ml)	SPIKE REC. (ug/ml)	SPIKE % RECOVERY
01/13/91	90-S63 S <sub>2</sub>	Pb As	4.0 2.0	3.46 1.55	86.6 77.5
	90-S86 S <sub>1</sub>	Pb · As	4.0 2.0	3.58 2.15	89.4 107
	90-S86 S <sub>2</sub>	Pb As	4.0	3.58 1.82	89.4 91.0
	90-S105 S <sub>1</sub>	Pb As	4.0	3.32 1.61	83.0 80.5
	90-S105 S <sub>2</sub>	Pb As	4.0	3.40 1.67	85.0 83.5
	90-S127 S <sub>2</sub>	Pb As	4.0	3.34 1.80	83.5 90.0

# POST-DIGESTION SPIKE ANALYSIS

DATE & INSTRUMENT	ANALYSIS ID	ANALYTES	SPIKE AMOUNT (UG/L)	SPIKE REC. (ug/L)	SPIKE % RECOVERY
01/11/91 GFAA	90-869	As	25.0	22.0	88.0
01/14/91 GFAA	90 <b>-</b> S114	As	25.0	25.0	100
GIM	90 <b>-</b> S111	Pb	25.0	27.1	108

SPIKE % RECOVERY:

[(sample+spike - unspiked sample)/spike added]\*100

APPROVED BY: QCS DATE: 1/24/91

EPA LOCATION	AS CONC. ug/g >80	MASS 9	AREAA cm2	S CONC.AS ug/cm2	CONC. ug/g >200	MASS g	AREAA cm2	S CONC.AS ug/cm2	CONC. ug/g >400	RSAM g	_	S CONC.AS ug/cm2	CONC. ug/g <400	MASS g	AREAA cm2	ug/cm2
1 RUG 2 RUG 2 MAT 3 ENTRY 3 RUG 3 CARPORT	95 180 520 300 150 240	.7 1.2 .5 2.9 .4 2.1	18813 25084 3819 25084 18813 25084	.00 .01 .07 .03 .00	49 140 290 580 95	.3 3.4 .1 .13	18813 25084 3819 25084 18813 25084	.00 .02 .01 .00 .00	180 230 460 250 190 180	.4 12.9 1.9 3.4 .45	18813 25084 3819 25084 18813 25084	.00 .12 .23 .03 .00	120 360 690 300 380 390	.05 11.7 2.6 1.2 .15	18813 25084 3819 25084 18813 25084	.00 .17 .47 .01 .00
55. 100.T.O.																
EPA LOCATION	PB CONC ug/g >80	MASS g	AREA cm2	PB CONCPB ug/cm2	conc. ug/g >200	RASS g	AREAP cm2	B CONC, P ug/cm2	ug/g >400.	MASS 9	AREAP cm2	B CONC.PB ug/cm2	conc. ug/g <400	MASS 9	AREA cm2	PB CONC ug/cm2

# APPENDIX B

CHEMICAL MASS BALANCE ANALYSIS RESULTS

#### TACOMA SLAG STUDY

# Sources Considered:

TACRD - Tacoma Road Dust

TACSD - Tacoma Soil

TACMV - Motor Vehicle Composite
TACPB - Leaded Vehicle Emissions
Kraft - Kraft Recovery Furnace
TACWD - Wood Combustion Profile

HTSLAG - House 1 Slag GHSLAG - House 2 Slag VRSLAG - House 3 Slag

#### Results:

- EPAVAC Almost perfect fit to 13 species using just the House l driveway slag profile, 99.7% mass explained. Also fit fairly well to the House 3 driveway slag profile.
- GHVAC Not fit by any combination of the above sources.

  Appears to contain very little slag. Relatively high in Ca, K, and Mn.
- VRVAC Also not fit by any combination of above sources. Relatively high in Si and Cl.

SAMPL	E CONTR E DURAT R SQU CHI SQU	ION	ON ESTIMATE 1.00 .12	S - SITE: START F PERCENT N	HOUR	DATE: 9.7 12	SIZE:	VERSION FINE	N: 7.
SOU		S	SCE(UG/M3)	STD ERR	TSTAT				
 12	HTSLA	.G	.9970	.0512					
MPACII	BED CON	СЕМТВ	ATION FINE/	COAPSE /TOT	PAT .				
	1.0+-		.1/		.0/	1.0+-	.1		
	UNCER	TAINT	Y/SIMILARIT	Y CLUSTERS	S VERSTON:	7.0 5	SUM OF CLU	STER SO	URCES
			TIONS - SI			E:	VERSIO		
SAMPL	E DURAT		1 00	START E			SIZE:	FINE	
	R SQU CHI SQU		1.00 .12	PERCENT N	MASS 9 DF	9.7 12			
	CHI DQC	AUG.			DI	12			
SPECI	ES	I	-MEAS		CALC	F	ATIO C/M-	RATI	O R/U
l	TOT	T	1.00000+-	.10000	.99704+-	.05118	.1.00+-	.11	0
13	AL	*	.01969+-	.00277	.01970+-	.00277	1.00+-	.20	.0
4	SI	*	.12620+-	.01678	.12603+-	.01674	1.00+-	.19	.0
.5	P		.00000<	.00007	.00000<	.00006	.00<	.00	. 0
16	S	*	.00000<	.00139	.00000<	.00159	.00<	.00	. 0
L7	CL	*	.00000<	.00021	.00000<	.00023	.00<	.00	. 0
<u>1</u> 9	K	#	.00419+-	.00048	.00387+-	.00044		. 15	5
20	CA	*	.02479+-	.00280	.02262+-	.00254	.91+-	.15	6
22	TI	*	.00279+-	.00028	.00266+-	.00027	.95+-	.13	3
23	V		.00000<	.00004	.00000<	.00003	.00<	.00	. 0
24	CR		.00065+-	.00007	.00070+-	.00007	1.09+-	.15	. 8
25	MN	*	.00000<	.00003	.00000<	.00002	.00<	.00	.0
26	FE	*	.17130+-	.01713	.16860+-	.01686	.98+-	.14	1
28	NI		.00000<	.00003	.00000<	.00002	.00<	.00	. 0
29	CU		.01784+-	.00178	.01826+-	.00183	1.02+-	.14	. 2
30	ZN	*	.00608+-	.00061	.00601+-	.00060	.99+-	.14	:
31	GA		.00000<	.00003	.00000<	.00003	.00<	.00	. 0
33	AS	*	.01581+-	.00158	.01705+-	.00170	1.08+-	.15	. :
34	SE		.00000<	.00002	.00000<	.00001	.00<	.00	. 1
35	BR	*	.00000<	.00006	.00000<	.00006	.00<	.00	. 0
37	RB		.00000<	.00002	.00000<	.00001	.00<	.00	. (
38	SR		.00009+-	.00002	.00012+~	.00001	1.31+-	.31	1.3
39	Y		.00000<	.00002	.00000<	.00002	.00<	.00	. (
40	ZR		.00000<	.00003	.00000<	.00003	.00<	.00	. (
42	MO		.00143+-	.00014	.00139+-	.00014	.97+-	. 14	:
46	PD		>00000	.00013	.00003<	.00012	.00<	.00	. :
47	AG		.00000<	.00016	.00000<	.00015	.00<	.00	. (
48	CD		.00004<	.00017	.00031<	.00016	8.19< 3		1.3
49	IN		.00000<	.00017	.00000<	.00016	.00<	.00	. (
50	SN		.00010<	.00019	.00049<	.00018	4.71<	8.72	1.
51	SB		.00305+-	00030	.00342+-		1.12+-	.16	
	BA		.00100+-	.00068	.00000+-		-+00,	.63	-1.
56	DA								
56	LA		.00137+-	.00093	.00111+-	.00085	. 81+-	. 83	:
			.00137+- .00000<	.00093 .00004	.00111+-	.00085	.81+- .00<	.83 .00	: ).

```
SOURCE CONTRIBUTION ESTIMATES - SITE: EPAVAC
                                                                     VERSION: 7.0
                                                    DATE:
SAMPLE DURATION
                                                           SIZE:
                              START HOUR
                                                                     FINE
      R SQUARE
                     1.00
                             PERCENT MASS
                                              100.1
     CHI SQUARE
                     .12
                                      DF
                                                 11
  SOURCE
                SCE (UG/M3)
     * TYPE
                              STD ERR
                                           TSTAT
      KRAFT
                     .0014
                                .0093
                                            .1548
   HTSLAG
                     .9999
                                        19.3964
12
                                .0516
______
MEASURED CONCENTRATION FINE/COARSE/TOTAL:
                  .1/
                                     .0/
                                                  1.0+-
       UNCERTAINTY/SIMILARITY CLUSTERS VERSION: 7.0
                                                         SUM OF CLUSTER SOURCES
SPECIES CONCENTRATIONS - SITE: EPAVAC
                                             DATE:
                                                             VERSION: 7.0
SAMPLE DURATION
                               START HOUR
                     1.00
                             PERCENT MASS
      R SQUARE
                                              100.1
     CHI SQUARE
                     . 12
                                       DF
                                                 11
SPECIES-----RATIO C/M---RATIO R/U
                  1.00000+- .10000 1.00135+- .05139
                                                            1.00+- .11
       TOT
1.
              T
                   .01969+-
                              .00277
                                        .01977+-
                                                    .00278
                                                             1.00+-
                                                                    .20
13
       AL.
                                                                              . 0
       SI
                   .12620+-
                              .01678
                                        .12639+-
                                                    .01679
                                                             1.00+-
                                                                     .19
15
       P
                   >00000<
                              .00007
                                         .00000<
                                                    .00006
                                                             .00<
                                                                     .00
                                                                              .0
                                                                     .00
16
       S
                   >000000
                              .00139
                                         .00024<
                                                    .00160
                                                              .00<
                                                                              .1
                                                                    .00
       CL
                   >00000<
                              .00021
                                         .00003<
                                                    .00023
                                                              .00<
17
                                                                     .15
                   .00419+-
                              .00048
                                         .00391+-
                                                    .00044
                                                              .93+-
19
       ĸ
                                                                             -.4
                   .02479+-
20
       CA
                               .00280
                                         .02269+-
                                                    .00255
                                                              .92+-
                                                                     . 15
                                                                             -.6
22
       TI
                   .00279+-
                              .00028
                                         .00266+-
                                                    .00027
                                                              .96+-
                                                                     .14
                                                                             -.3
                                                                     .00
                   .00000<
                                         .00000<
                                                    .00003
                                                              .00<
23
       v
                               .00004
                                                                              . 0
24
       CR
                   .00065+-
                               .00007
                                         .00071+-
                                                    .00007
                                                             1.09+-
                                                                     .15
                                                                              .6
25
       MN
                   .00000<
                               .00003
                                         >00000
                                                    .00002
                                                             .00<
                                                                     .00
                                                                              . 0
                                                              .99+-
                                         .16909+-
                                                    .01691
                                                                             -.1
26
       FE
                   .17130+-
                               .01713
                                                                     .14
                                                    .00003
28
       NI
                                         .00000<
                                                              .00<
                   >00000<
                               .00003
                                                                     .00
                                                                              .0
                                         .01831+-
29
       CII
                   .01784+-
                               .00178
                                                    .00183
                                                             1.03+-
                                                                     .15
30
       ZN
                   .00608+-
                               .00061
                                         .00603+-
                                                    .00060
                                                             .99+-
                                                                     .14
31
       GA
                   >00000.
                               .00003
                                         >00000.
                                                    .00003
                                                              .00<
                                                                     .00
                                                                              . 0
                   .01581+-
                                         .01710+-
                                                    .00171
                                                             1.08+-
                                                                              .6
33
       AS
                               .00158
                                                                     . 15
                                         .00000<
                                                             .00<
       SE
                   .00000<
                               .00002
                                                    .00001
                                                                     .00
34
35
                   >00000<
                               .00006
                                         .00000<
                                                    .00006
                                                              .00<
                                                                     .00
       BR
                                                                              . 0
37
       RB
                   >000000
                               .00002
                                         .00000<
                                                    .00001
                                                              .00<
                                                                     .00
                                                                              . 0
38
       SR
                   .00009+-
                               .00002
                                         .00012+-
                                                    .00001
                                                             1.32+-
                                                                     .31
                                                                             1,2
                                                              .00<
                                                                     .00
39
                   .00000<
                               .00002
                                         .00000<
                                                    .00002
                                                                              .0
       Y
40
       ZR
                   >00000
                               .00003
                                         .00000<
                                                    .00003
                                                              .00<
                                                                     .00
                                                                              . 0
                   .00143+-
                               .00014
                                                    .00014
42
       MO
                                         .00140+-
                                                              .98+-
                                                                     .14
                                                                             -.2
                   ,00000<
46
       PD
                               .00013
                                         .00003<
                                                    .00012
                                                              .00<
                                                                     .00
47
       AG
                    .00000<
                               .00016
                                         .00000<
                                                    .00015
                                                              .00<
                                                                     .00
                                                                              .0
                                                             8.22< 36.78
48
       CD
                   .00004<
                               .00017
                                         .00031<
                                                    .00016
                                                                             1.2
                   >00000
                                                    .00016
                                                             .00<
       IN
                               .00017
                                         .00000<
                                                                              . 0
                                         .00049<
                                                             4.72< 8.75
50
       SN
                    .00010<
                               .00019
                                                    .00018
                                                                             1.5
51
       SB
                    .00305+-
                               .00030
                                         .00343+-
                                                    .00034
                                                             1.12+-
                                                                    .16
                                                                              . 8
                                                             .00+-
56
       BA
                   .00100+-
                               .00068
                                         .00000+-
                                                    .00063
                                                                    .63
                                                                            -1.1
                                                                    . 83
                                                    .00085
                                                              .81+-
57
       LA
                    .00137+-
                               .00093
                                         .00111+-
                                                                             -.2
80
       HG
                    .00000<
                               .00004
                                         >00000.
                                                    .00003
                                                              .00<
                                                                     .00
                                                                              .0
                                                    .00099
                                                             1.10+-
       PB
                    .00906+-
                               .00091
                                         .00995+-
                                                                    . 16
                                                                              . 7
```

SAMPL	E CONTR E DURAT R SQU CHI SQU	ION IARE	ON ESTIMATE .98 .60	S - SITE: START HO PERCENT MA	UR	DATE: 1.2 11	SIZE:	VERSIC FINE	ON: 7.
	RCE * TYPE	S	CE(UG/M3)		TSTAT				
 06	KRAFI	- <b></b> -	.0015		.1674				
10 "	VRSLA	.G	.8109	.0419	19.3512 				
ÆASU	IRED CON	ICENTE	ATION FINE	COARSE/TOTA	AL:				
	1.0+-		.1/	.0+-		1.0+-	.1		
	UNCER	TAINI	Y/SIMILARIT	Y CLUSTERS	VERSION:	7.0	SUM OF CLUS	STER SC	URCES
	IES CONC		ATIONS - SI	TE: EPAVAC		 E:	VERSION	 N: 7.0 FINE	<b></b> -
		JARE	.98	PERCENT MA	ASS 8	1.2			
	CHI SQU	JARE	.60		DF -	11			
PECI	ES	7	MEAS		CALC		RATIO C/M~·	RAT1	[O R/
	TOT		1.00000+-		.81232+-				-1.
.3	AL	*	.01969+-	.00277	.02687+-	.00372	1.36+-	.27	1.
4	SI	*	.12620+-	.01678	.14742+-	.01959		. 22	
.5	P		.00000<	.00007	.00000<	.00006	.00<	.00	
6	S	*	.00000<	.00139	.00024<	.00141	.00<	.00	
.7	CL	*	.00000<	.00021	.00003<	.00020	.00<	.00	
9	K	*	.00419+-	.00048	.00384+-	.00043	.92+-	.15	
20	CA	*	.02479+-	.00280	.02542+-	.00286	1.03+-	.16	
22	TI	*	.00279+-	.00028	.00246+-	.00025	.88+-	.12	
23	v		.00000<	.00004	.00000<	.00003	.00<	.00	
24	CR		.00065+-	.00007	.00034+-	.00003	.53+-	.07	-4.
25	MN	*	.00000<	.00003	.00000<	.00002	.00<	.00	
26	FE	*	.17130+-	.01713	.15723+-	.01572	.92+-	. 13	
28	NI		.00000<	.00003	.00000<	.00002	.00<	.00	
29	CU		.01784+-	.00178	.01095+-	.00110	.61+-	.09	-3.
10	ZN	*	.00608+-	.00061	.00684+-	.00068	1.13+-	.16	
31	GA		.00000<	.00003	.00000<	.00002	.00<	.00	
3	AS	*	.01581+-	.00158	.01342+-	.00134	.85+-	.12	-1.
4	SE		.00000<	.00002	.00000<	.00001	.00<	.00	
35	BR	*	.00000<	.00006	.00000<	.00005	.00<	.00	
37	RB		.00000<	.00002	.00000<	.00001	,00<	.00	
88	SR "		-+60000	.00002	.00011+-	.00001	1.22+-	.28	
9	Y		.00000<	.00002	.00000<	.00001	.00<	.00	
0	ZR		>00000<	.00003	.00000<	.00003	.00<	.00	
2	MO		.00143+-	.00014	.00088+-	.00009		.09	-3.
6	PD		.00000<	.00013	.00008<	.00010		.00	
7	AG		.00000<	.00016	.00000<	.00012		.00	
8	CD		.00004<	.00017	.00026<	.00013		1.16	1.
	IN		.00000<	.00017	.00000<	.00013		.00	
19	SN		.00010<	.00019	.00057<	.00015	·		2.
			.00305+-	.00030	.00363+-	.00036	1.19+~	. 17	1.
50	SB								
50 51			.00100+-	.00068	.00008+-	.00051		. 51	-1.
49 50 51 56 57	SB					.00051		. 51 . 50	-1. -1.
50 51 56	SB BA		.00100+-	.00068	.00008+-	.00051	.00+~		

```
SOURCE CONTRIBUTION ESTIMATES - SITE: EPAVAC
                                                                       VERSION: 7.0
                                                              SIZE:
SAMPLE DURATION
                                START HOUR
                                                                       FINE
      R SQUARE
                       .98
                              PERCENT MASS
                                                 81.2
     CHI SQUARE
                       .55
                                        DF
                                                   12
 SOURCE
                SCE(UG/M3)
     * TYPE
                               STD ERR
                                             TSTAT
10
       VRSLAG
                      .8116
                                  .0417
                                           19.4601
MEASURED CONCENTRATION FINE/COARSE/TOTAL:
                              .0+-
                                                   1.0+-
       1.0+-
                  .1/
                                                               . 1
       UNCERTAINTY/SIMILARITY CLUSTERS VERSION: 7.0
                                                            SUM OF CLUSTER SOURCES
SPECIES CONCENTRATIONS - SITE: EPAVAC
                                               DATE:
                                                                VERSION: 7.0
SAMPLE DURATION
                                START HOUR
                                                              SIZE:
                                                                       FINE
                       .98
                              PERCENT MASS
      R SQUARE
                       .55
                                        DF
     CHI SQUARE
                                                  12
SPECIES-----RATIO C/M---RATIO R/U
                                                     .04170
                                          .81158+-
1
       TOT
              T
                   1.00000+-
                                .10000
                                                                .81+- .09
                                                                               -1.7
                    .01969+-
                                .00277
                                          .02689+-
                                                      .00372
                                                               1.37+-
                                                                       . 27
13
       AL
                                                                                1.6
                                .01678
                                          .14755+-
                                                               1.17+-
                    .12620+-
                                                      .01961
                                                                       . 22
                                                                                . 8
14
       ST
15
       P
                    >00000<
                                .00007
                                          >00000
                                                      .00006
                                                                .00<
                                                                       .00
                                                                                 .0
      . 8
                    .00000<
                                .00139
                                          .00000<
                                                      .00141
                                                                .00<
                                                                       .00
                                                                                 .0
16
                                                      .00020
                                                                .00<
17
       CL
                    >00000<
                                .00021
                                          .00000<
                                                                       .00
                                                                                 α
                                                                .91+-
                                                                       . 15
19
                    .00419+-
                                .00048
                                          .00381+-
                                                      .00043
                                                                                -.6
       K
       CA
                    .02479+-
                                .00280
                                          .02544+-
                                                      .00286
                                                               1.03+-
                                                                       .16
                                                                                 . 2
20
22
       ΤI
                    .00279+-
                                .00028
                                          .00246+-
                                                      .00025
                                                                .88+-
                                                                       .12
                                                                                -.9
23
                    >00000
                                .00004
                                          >00000
                                                      .00003
                                                                .00<
                                                                       .00
                                .00007
                    .00065+-
                                          .00034+-
                                                                .53+-
                                                                       .07
24
       CR
                                                      .00003
                                                                               -4.2
25
       MN
                    >00000
                                .00003
                                          .00000<
                                                      .00002
                                                                .00<
                                                                        .00
                                                                                 .0
       FE
                    .17130+-
                                .01713
                                          .15737+-
                                                      .01574
                                                                .92+-
                                                                       .13
                                                                                -.6
26
                                                                .00<
                                                                       .00
                                .00003
                                          >00000<
                                                      .00002
                                                                                 .0
28
       NI
                    .00000<
29
       CU
                    .01784+-
                                .00178
                                          .01096+-
                                                      .00110
                                                                .61+-
                                                                        .09
                                                                               ~3.3
                                :00061
                                                               1.13+-
30
       Z.N
                    .00608+-
                                          .00685+-
                                                      .00068
                                                                       . 16
                                                                                . 8
                                                      .00002
31
       GΑ
                    >00000.
                                .00003
                                          >00000
                                                                .00<
                                                                        .00
                                                                                 .0
                                                      .00134
                                                                .85+-
33
       AS
                    .01581+-
                                .00158
                                          .01343+-
                                                                       . 12
                                                                               -1.1
                                                                       .00
                    >00000.
                                .00002
                                          .00000<
                                                      .00001
                                                                .00<
                                                                                 .0
34
       SE
35
                    .00000<
                                .00006
                                          .00000<
                                                      .00005
                                                                .00<
                                                                        .00
       BR
37
       RB
                    .00000<
                                .00002
                                          .00000<
                                                      .00001
                                                                .00<
                                                                        .00
                                                                                 .0
38
       SR
                    .00009+-
                                .00002
                                          .00011+-
                                                      .00001
                                                               1.22+-
                                                                        .28
                                                                                 .9
39
       Y ..
                    .00000<
                                .00002
                                          .00000<
                                                      .00001
                                                                .00<
                                                                        .00
                                                                                 .0
                                                                .00<
                                                                        .00
       ZR
                    .00000<
                                .00003
                                          >00000.
                                                      .00003
                                                                                 . 0
40
42
       MO
                    .00143+-
                                .00014
                                          .00088+-
                                                      .00009
                                                                .61+-
                                                                        .09
                                                                               -3.3
                                .00013
                                          .00007<
                                                      .00010
                                                                .00<
46
       PD
                    .00000<
                                                                        .00
                                                                                . 4
                                                                .00<
47
       AG
                    >00000
                                .00016
                                          .00000<
                                                      .00012
                                                                        .00
                                                                                 .0
48
       CD
                    .00004<
                                .00017
                                          .00026<
                                                      .00013
                                                               6.96< 31.16
                                                                                1.1
                                          .00000<
                    >00000
                                .00017
                                                      .00013
                                                                .00<
                                                                      .00
                                                                                . 0
49
       IN
50
                    .00010<
                                .00019
                                          .00057<
                                                      .00015
                                                               5,52< 10.12
                                                                                2.0
51
       SB
                    .00305+-
                                .00030
                                          .00363+-
                                                      .00036
                                                               1,19+-
                                                                       . 17
                                                                                1.2
                                                                        .51
56
       BA
                    .00100+-
                                .00068
                                           .00008+-
                                                      .00051
                                                                .08+-
                                                                               -1.1
57
       LA
                    .00137+-
                                .00093
                                          .00000+-
                                                      .00069
                                                                .00+-
                                                                               -1.2
                                                                        .00
                                .00004
                                                      .00002
                                                                 .00<
80
       HG
                    >00000<
                                          >000000
                                                                                .0
82
       PB
                    .00906+-
                                .00091
                                           .00898+-
                                                      .00090
                                                                 .99+-
                                                                        .14
                                                                                -.1
```

B.5


SAMPL	E DURAT R SQU	ION JARE	ON ESTIMATE .84 13.64	START HO PERCENT MA	UR	DATE:	SIZE:	VERS FINE	ION: 7.0
SOU	JRCE * TYPE	S	SCE(UG/M3)	STD ERR	TSTAT				
01	TACRE	· <del>-</del> ~	.2351	.0236	9.9814				
02	TACSI		.0257	.0046	5.5498				
06	KRAFT		.1190	.0153	7.7556				
MEASU	RED CON 1.0+-		ATION FINE/	COARSE/TOTA		1.0+-	.1		
			•		·				
	UNCE	RTAINT	Y/SIMILARIT	Y CLUSTERS	VERSION:	7.0	SUM OF CLU	STER	SOURCES
					<u>-</u>				·
			TIONS - SI			:	VERSIO		
SAMPI	LE DURAT	JARE	9.6	START HO	)UK .cc 30		SIZE:	FINE	•
	CHI SQL			FERCENT PA	DF 30	5			
	•								
			-MEAS						
1	TOT	T	1.00000+-		.37987+-				-6.0
13	AL Si	*	.01525+~		.02210+- .06737+-				2.5 1.3
.14 15	P	-	.05490+~ .00055+~		.00737+-			.42	7.0
16	S	*	.02174+~	.00246	.02054+-	.00200		.14	4
17	CL	*	.00246+-		.00262+-	.00040			.3
19	K		.02522+~	.00284	.00479+-	.00034			-7.2
20	CA		.09309+-		.00598+-	.00057		.01	-8.3
22	TI	*	.00325+-	.00033	.00128+-	.00011		.05	-5.7
23	V		.00007+-		.00006+-	.00001	.92+-	. 52	~.1
24	CR		.00024+-	.00002	.00012+-	.00001	. 53+-	.08	-4.0
25	MN		.00115+-	.00012	.00025+-	.00002	.21+-	.03	-7.7
26	FE	*	.01808+-	.00181	.01356+-	.00122	.75+-	.10	-2.1
28	NI		.00006+-	.00001	.00007+-	.00005		.91	.3
29	CU		.00057+-	.00006	.00035+-	.00003		.08	-3.4
30	ZN	*	.00180+-	.00018	.00103+-	.00008		.07	-3.9
31	GA		.00000<	.00001	.00001<	.00000			.7
33	AS		.00033+- .00000<	.00004	.00008+-	.00002	-	.06	-6.6
34 35	SE BR			.00001	.00001< .00009+-	.00001			1.4 -3.9
33 37	RB ·		.00018+-	.00002 .00001	.00009+-	.00001			-3.9 .7
38	SR		.00052+-	.00001	.00010+-	.00001		.03	-7.9
39	Y		.00000<	.00001	.00001<	.00000		.00	1.1
40	ZR		.00021+-	.00002	.00004+-	.00003		. 14	-4.6
42	MO		.00002+-	.00002	.00003+-	.00002			.2
46	PD		.00000<	.00006	.00004<	.00002		.00	.7
47	AG		.00003<	.00008	.00004<	.00003	1.33<	3.34	.1
48	CD		.00010+-	.00008	.00004+-	.00002		.43	6
49	IN		.00000<	.00010	.00007<	.00007		.00	.6
50	SN		.00000<	.00012	.00007<	.00002		.00	. 6
51	SB		.00000<		.00007<	.00007		.00	. 4
56	BA		.00163+-	.00056	.00022+-	.00013		.09	-2.5
57	LA		.00133+-	.00074	.00037+-	.00027		. 25	-1.2
80	HG		.00000<	.00001	.00001<	.00000		.00	.6
82	PB	*	.00051+-	.00005	.00071+-	.00005	1.40+-	. 17	2.8

```
SAMPLE DURATION
                               START HOUR
                                                            SIZE:
                                                                     FINE
      R SQUARE
                             PERCENT MASS
     CHI SQUARE
                    22.08
                                    DF
 SOURCE
    * TYPE
                SCE(UG/M3)
                              STD ERR
                                            TSTAT
                     .2740
01
       TACRD
                                 0260
                                          10.5459
02
       TACSD
                     .0107
                                 .0036
                                           2.9421
06
       KRAFT
                     .0701
                                 .0096
                                           7.3248
MEASURED CONCENTRATION FINE/COARSE/TOTAL:
       1.0+-
                  .1/
                             .0+-
                                                  1.0+-
                                                              .1
                                                          SUM OF CLUSTER SOURCES
       UNCERTAINTY/SIMILARITY CLUSTERS VERSION: 7.0
SPECIES CONCENTRATIONS - SITE: VRVAC
                                              DATE:
                                                              VERSION: 7.0
SAMPLE DURATION
                               START HOUR
                                                            SIZE:
                                                                     FINE
                      .74
                              PERCENT MASS
                                                35.5
      R SQUARE
     CHI SQUARE
                    22.08
                                       DF
SPECIES-----RATIO C/M----RATIO R/U
                                         .35483+-
                                                   .02523
1
       TOT
              Т
                  1.00000+-
                              .10000
                                                              .35+- .04
                                                    .00206
                                                              1.52+-
                              .00206
                                         .02240+-
13
       ΑL
                   .01476+-
                                         .07570+-
                                                    .00740
                                                              .90+-
                   .08365+-
                               .01116
                                                                     .15
                                                                              -.6
14
       ST
15
       P
                   .00000<
                               .00007
                                         .00050<
                                                     .00013
                                                               .00<
                                                                     .00
                                                                              3.4
                                                              1.24+- .19
16
       S
                   .01005+-
                               .00117
                                         .01244+-
                                                    .00118
                                                                             1.4
                                         .00165+-
                                                    .00024
                                                              .28+-
                               .00069
                                                                     .05
17
       CL
                   .00588+-
                                                                             -5.8
19
       K
                   .00872+-
                               .00099
                                         .00392+-
                                                    .00028
                                                               .45+-
                                                                     .06
                                                                             -4.7
                   .04664+-
                                                              .14+-
20
                               .00528
                                         .00673+-
                                                    .00066
                                                                     .02
                                                                             -7.5
       CA
                                                               .39+-
                                         .00137+-
                                                     .00013
                                                                     .05
22
       ΤI
                    .00355+-
                               .00035
                                                                             -5,8
23
       v
                    .00004<
                               .00004
                                         .00007<
                                                     .00001
                                                              1.94< 2.25
                    .00027+-
                                         .00012+-
                                                     .00001
                                                              .43+-
                                                                     .06
                                                                             -5.2
24
       CR
                               .00003
                    .00027+-
                                         .00026+-
                                                     .00002
                                                               .96+-
                                                                     .13
25
       MN
                               .00003
                                         .01461+-
                                                     .00139
                                                               .90+- .12
26
       FE
                    .01630+-
                               .00163
                                                                              -.8
                                         .00006+-
                                                     .00003
                                                              1.97+- 1.35
28
                    .00003+-
                               .00001
       NT
                                                                               . 9
                                                                             -6.1
29
       CU
                    .00069+-
                               .00007
                                         .00025+-
                                                     .00002
                                                              .37+- .05
30
       ZN
                    .00124+-
                               .00012
                                         .00064+-
                                                     .00005
                                                               .52+-
                                                                     .06
                                                                             -4.5
                                                     .00000
                                                               .00<
31
       GA
                    >00000
                               .00001
                                         >00000.
                                                                      .00
                                         .00009+-
                                                     .00002
                                                               . 52+-
33
       AS
                    .00017+-
                               .00003
                                                                     .15
                                                                             -2.4
                    >00000.
                                         .00001<
                                                     .00000
                                                               .00<
                                                                     .00
34
       SE
                               .00001
                                                                              1.0
35
       BR
                    .00004+-
                               .00001
                                         .00006+-
                                                     .00001
                                                              1.61+-
                                                                      .44
                                                                              2.0
37
                                         .00003<
                                                     .00001
                                                              9.31< 37.30
       RB
                    >00000
                               .00001
                                                                              1.9
                                                     .00001
38
       SR
                    .00014+-
                               .00002
                                          .00011+-
                                                               .81+- .13
                                                                             -1.3
                                                     .00000
                                                               .00<
39
       Y
                    >00000<
                               .00002
                                         .00001<
                                                                      .00
                                                                               .7
                    .00174+-
                                         .00003+-
                                                     .00002
                                                               .01+-
40
       ZR
                               .00017
                                                                      .01
                                                                             -9.8
42
                    .00002<
                               .00003
                                         .00003<
                                                     .00001
                                                              1.46< 2.56
       PD
                    >00000<
                               .00008
                                         .00003<
                                                     .00001
                                                               .00<
                                                                     .00
46
                                                                               . 3
47
                                                     .00002
       AG
                    .00018+-
                               .00010
                                         .00003+-
                                                               .18+-
                                                                      .15
                                                                             -1.4
                                                     .00001
       CD
                    .00024+-
                               .00012
                                         .00003+-
                                                               .11+-
                                                                             -1.8
                                                               .00<
                                                                      .00
                                                     .00004
49
       IN
                    >00000.
                               .00014
                                         .00005<
                                                                            ..... 3
                                                                      .26
50
       SN
                    .00017<
                               .00018
                                         .00004<
                                                     .00002
                                                               .23<
                                                                              -.7
51
                    .00058+-
                               .00022
                                         .00004+-
                                                     .00005
                                                               .08+-
                                                                     .08
                                                                             -2.3
       SB
56
       BA
                    .00033<
                               .00086
                                          .00015<
                                                     .00009
                                                               .47< 1.25
                                                                              -.2
57
                                                     .00017
                                                               .64<
       LA
                    .00039<
                               .00119
                                         .00025<
                                                                     2.02
                                                                              -.1
80
       RG
                    .00000<
                               .00002
                                         .00001<
                                                     .00000
                                                               .00<
                                                                     .00
                                                                               4
82
       PB
                    .00032+-
                               .00004
                                          .00052+-
                                                     .00004
                                                              1.64+-
                                                                              3.6
```

SOURCE CONTRIBUTION ESTIMATES - SITE: VRVAC

VERSION: 7.0


DATE:



Solid Bars are Calculated concentrations.

Dashed Lines are Measured Concentrations.


Asterisk are the Fitting Species



Solid Bars are Calculated concentrations.

Dashed Lines are Measured Concentrations.

Asterisk are the Fitting Species



Solid Bars are Calculated concentrations.

Dashed Lines are Measured Concentrations.

And State and the Fitting Species

srce	part	revsion			refe	erence
code	size	date	source description		author	date
5712	<del></del>	01/17/91	Tacoma/House 3 Hsehld Vacuum	Wado	John	01/91
		• •				•
5713	${f T}$	01/17/91	Gig Harbor/House 2 Hsehld Vac	Wade,	John	01/91
5714	T	01/17/91	Gig Harbor/House 2 EPA Vac	Wade,	John	01/91
5715	T	01/17/91	Tacoma/House 3 Driveway Slag	Wade,	John	01/91
5716	${f T}$	01/17/91	Gig Harbor/House 2 Drvwy Slag	Wade,	John	01/91
5717	T	01/17/91	Tacoma/House 1 Driveway Slag	Wade,	John	01/91

source description

reference

author

date

Tacoma/House 3 Hsehld Vacuum

Wade, John

01/91

	PERCENT	COMPOSI	TION	
SPECIES	FINE	COARSE	TOTAL	
Al	•	•	1.4760 +20	164
Si			8.3650 +- 1.11	.60
P			.0000 +00	74
S			1.0050 +11	.72
Cl			.5879 +06	<b>i92</b>
K			.8720 +09	93
Ca			4.6640 +52	278
Ti			.3554 +03	<b>355</b>
v			.0035 +00	)40
Cr			.0270 +00	)27
Mn		·	.0269 +00	)27
Fe		•	1.6300 +16	330
Ni		•	.0029 +00	)13
Cu			.0694 +00	
Zn		•	.1240 +01	
Ga			.0000 +00	)10
As			.0166 +00	
Se			.0000 +00	
Br	<b></b>		.0040 +00	
Rb			.0003 +00	)12
Sr			.0142 +00	)17
Y			.0000 +00	
Zr			.1741 +01	
Mo			.0020 +00	
Pd			.0000 +00	
Ag	•		.0183 +01	104
Cd			.0244 +01	
In		<b>■</b> 10 Mg .		143
Sn				178
Sb				223
Ra			U336 + 00	057
Ba	•			857
La				188
Hg	•			016
Pb		ı	.0319 +00	040
_		·		
Sum			19.6410	

source description

reference author date

5713 T 01/17/91 Gig Harbor/House 2 Hsehld Vac Wade, John

01/91

## PERCENT COMPOSITION

SPECIES		FINE	K C B N	cc	DARSE		TC	TAI	<b>,</b>
Al						1	.5250	+-	.2075
Si						5	4900	+-	.7292
P							.0549	+-	.0144
S					<b>V</b>	2	.1740	+-	.2461
Cl			÷	•			.2456	+-	.0345
ĸ					•	2	.5220	+-	.2837
Ca						9	.3090	+-	1.0450
Ti		•					.3248	+-	.0325
v	•						.0070	+-	.0037
Cr							.0236	<b>+-</b>	.0024
Mn	•					•	.1151		.0115
Fe							.8080		.1808
Ni							.0057		.0011
Cu							.0566		.0057
Zn	•						.1803	+	.0180
Ga							.0000		.0008
As							.0335		.0035
Se		•					.0000	+-	.0006
Br			•				.0180	+-	.0018
Rb							.0027	+-	.0009
Sr						1	.0524	+	.0052
Y	••						.0000	+	.0012
Zr							.0208	+-	.0023
Mo					-	,	.0025	+-	.0020
Pd			•				.0000	+-	.0062
Ag							.0031	+-	.0075
Cd		,					.0096		.0083
In				*			.0000	+-	.0096
Sn					,		.0000	+-	.0118
Sb							.0000	+-	.0143
Ba				;			.1626		.0557
La							.1332		.0740
Hg							.0000	+-	.0012
Pb	. •		•				.0507	+-	.0051

Sum

source description

reference author date

5714 T 01/17/91 Gig Harbor/House 2 EPA Vacuum Wade, John

01/91

#### PERCENT COMPOSITION

SPECIES	FINE	NT	COARSE	TOTA	AL .
Al				1.9690 +-	.2768
Si				12.6200 +-	1.6780
P	-			.0000 +~	0066
S				.0000 +-	.1391
Cl				.0000 +~	.0213
K				.4186 +-	
Ca				2.4790 +-	.2795
Ti				.2785 +-	0278
V				.0000 +-	.0036
Cr				.0648 +-	.0065
Mn	•		•	.0000 +~	
Fe				17.1300 +-	
Ni				.0000 +-	
Cu	•			1.7840 + <del>,</del>	
Zn				.6081 +-	0608
Ga				.0000 +-	
As				1.5810 +-	
Se				.0000 +-	
Br				.0000 +-	
Rb				.0000 +-	0017
sr				.0088 +-	
Υ				.0000 +-	
Zr	•			.0000 +-	
Мо			•	.1430 +-	
Pd		*		.0000 +-	0134
Ag		ν,		.0000 +-	
Cd				.0038 +-	
In				.0000 +-	0171
Sn				.0104 +-	0189
Sb	•			.3049 +-	0305
Ва				.1001 +-	
La	·		•	.1372 +-	0927
Hg				.0000 +-	0036
Pb				.9062 +-	0906
•					

Sum

source description

reference

date author

5715 T 01/17/91 Tacoma/House 3 Driveway Slag Wade, John

#### PERCENT COMPOSITION

SPECIES	FINE	COARSE	TOTAL
Al			3.3130 +4584
Si	•		18.1800 +- 2.4160
P			.0000 +0070
S			.0000 +1733
CĪ			.0000 +0248
ĸ			.4689 +0534
Ca			3.1350 +3527
Ti		•	.3032 +0303
V			.0000 +0038
Cr			.0421 +0042
Mn			.0000 +0027
Fe		•	19.3900 +- 1.9390
Ni			.0000 +0024
Cu			1.3510 +1351
Zn	•		.8440 +0844
Ga			.0000 +0027
As			1.6550 +1655
Se			.0000 +0015
Br			.0000 +0064
Rb			.0000 +0015
Sr			.0132 +0016
<b>Y</b> "			.0000 +0018
Zr			.0000 +0034
Mo			.1081 +0108
Pđ	·	·	.0092 +0127
Ag			.0000 +0148
Cd		•	.0326 +0163
In			.0000 +0160
Sn			.0707 +0179
Sb			.4477 +0448
Ba			.0097 +0626
La			.0000 +0853
Hg	•		.0000 +0030
Pb			1.1070 +1107

Sum

source description

reference author

date

5716 T 01/17/91 Gig Harbor/House 2 Drvwy Slag Wade, John

#### COMPOSITION PERCENT

SPECIES	FINE	COARSE	TOTAL
Al	·		1.5380 +2221
Si			11.9500 +- 1.5880
$\mathbf{P}^{'}$			.0000 +0063
s			.0000 +1546
Cl			.0000 +0227
K	•		.3043 +0350
Ca			2.6290 +2961
Ti.	·		.2494 +0249
v			.0000 +0034
Cr			.0352 +0035
Mn			.0000 +0026
Fe	·		19.5600 +- 1.9560
Ni			.0000 +0027
Cu	·		1.8710 +1871
Zn			1.3990 +1399
Ga			.0000 +0031
As			4.6160 +4616
Se			.0000 +0022
Br			0000 +0165
Rb			.0000 +0024
Sr			.0045 +0016
Υ		4	.0000 +0019
Zr			.0000 +0038
Mo			.1750 +0175
Pd			.0306 +0153
Ag			.0296 +0169
Cd			.0365 +0183
In			.0000 +0184
Sn			.0370 +0202
Sb			.5535 +0553
Ba		•	.0008 +0651
La	•	•	.0000 +0902
Нg			.0000 +0036
Pb			1.1620 +1162

Sum

source description

reference author date

5717 T 01/17/91 Tacoma/House 1 Driveway Slag

Wade, John

01/91

#### PERCENT COMPOSITION

SPECIES	FINE	COARSE	TOTAL
Al			1.9760 +2776
Si			12.6400 +- 1.6790
P		ý.	.0000 +~ .0063
s			.0000 +1595
Cl		•	.0000 +0227
K			.3879 +0442
Ca			2.2690 +2552
Ti			.2663 +0266
v		•	.0000 +0034
Cr			.0706 +0071
Mn			.0000 +0025
Fe			16.9100 +- 1.6910
Ni			.0000 +0025
Cu	•		1.8310 +1831
Zn			.6032 +0603
Ga		. ·	.0000 +0026
As			1.7100 +1710
Se			.0000 +0015
Br		Ÿ.	.0000 +0065
Rb			.0000 +0014
Sr		•	.0116 +0015
<b>Y</b> "			.0000 +0017
Zr	•		.0000 +0032
Mo			.1396 +0140
Pd			.0027 +0125
Ag	•	:	.0000 +0146
Cd			.0312 +0160
In			.0000 +0161
Sn			.0491 +0178
Sb			.3426 +0343
Ва			.0000 +0629
La		ř	.1111 +0853
Hg			.0000 +0027
Pb		•	.9949 +0995
		•	

Sum

#### APPENDIX C

CHAIN OF CUSTODY RECORD FOR FIELD SAMPLING

NOTE: In this section, for confidentiality, house addresses are covered and replaced with House 1, House 2 or House 3.

The addresses remain on the original chain of custody.

NEA, INC.

10950 S.W. 5TH STREET SUITE 310

BEAVERTON, OREGON 97005

Phone (503) 643-4661

## CHAIN OF CUSTODY RECORD

Fax (503)643-4039	<del>)</del>																		
PROJECT PROJECT NAME										•					REMAR	<b>⟨S</b>	4 2 .)		= 25800
316-001 TACOM	A SL	a9 S	Stuc	) <u>Y                                    </u>											4100	20	7 20		= 2580c = 645c
SAMPYERS (Signature)	./-	10	، رمے	20			j	j							Ket	715=10	XIO	u	- 643 c
TEMP. THAMAY   Z. BULOLO SAMPLE IDENTIFICATION	DATE 9	7145	<u> </u>		-														
SANFLE IDENTIFICATION			SAPE.	REAK					<del></del>	<del>- </del>	<u> </u>	<del>                                     </del>		<u> </u>					
Refridge TS 112 7901	11/21		<u>/</u>					_	_	_					Hou	sel-T	acom	<u>a</u>	
lon TS 1127902	11/27	11:25	V	ļ			_	_											······································
Carpet TS 1127903	11/27	11:30	V					_											
acuum TS1127904	11127	かごろ	<u>/</u>				·	_									·····		
acoun Rine [5] 127905	11/27	13:30		1												·			
Driveway Slag TSH27906	11/27	12:40	STAB.																
nurvay Slag TS 1127107	11/27	1300	/																
and Composite #1 TS112798				cono															
Kard #2 TS1127909	11/27											,							
Yard #3 TS 1127910	11/27	13:30		1				9								,			
Yard #4 TS 1127911	11/27	13:45		V															
Soil core Rine TS 1127912	11/27	1400	Blank																
																-			
									$\neg \vdash$										
							101	TAL NO	. OF C	MIATHO	RS	·	136				7		
Relinquished by:		/ Time	Rec	eived b	y: (si	ignatur	e De	R	eling	ished	by:	2.18		l		eceived by Rell	; (Signat	ure)	
Relinquished by:	Date	/ Time /90 /83	Rec	e ived b	y: (Si	ignatur Han	re) MY	R	elingu	dshed Ham	by: MG		1	ate/Tin	e R	ece ived by	: (Signat	gre)	
<del></del>		Shipped		pped by						(Sign		)		Received					Date/Time
Method of Shipment:  Distribution: Original Accome	Date	Shipped	Shi	pped by	: (Sig	gnature				7,		)					AN	cet	

Distribution: Original Accompanies Shipment; Copy to Field Files

A, INC.

10950 S.W. 5TH STREET SUITE 310

BEAVERTON, OREGON 97005

Phone (503)643-4661 Fax (503)643-4039

14x (303)043 4033															
PROJECT PROJECT NAME										-					REMARKS
316-001 TACOMA SL	AG	STIL	<b>Y</b>								:				
SAMPLERS (Signature)	<u>'                                    </u>	<u> </u>	<del>}                                    </del>	/1	1					ŀ					·
SAMPLERS (Signature) Rich Harmy Den Kep	lli	i A	150	Vale	<u> </u>										
	DATE	TIME	GRAB	COMP							<u> </u>				
Yard Soil #1 TS1127913 1	1/27	4:30		V											House 2-Gig Harbor
		4140		V											
Kasal #3 TS1127917 1		4:50		V											
	11/27			1/											
1212 2011 1 13 112/110 11		4:30								1	1			-	
										-}-	<del>                                     </del>				
The state of the s		4.30									-				
Spatula Rinse 75/127919 1	1121	5:20	blank							_	╬-			<del>-   · · '</del>	
Sol Core Sump. Ringe Him TS107900	11/27	5:30	blank									<del>  </del> -			
	7								_						
															·
				l											
											·				
										_	-				
							· ,	OTAL	un ne	CONTAIL			8		
\					<u> </u>	<u> </u>		OIAL .			.,			i	
Relinquished by:		/ Time	Rec	eived b	y: (S	ignatu	ice)	·	Relin	ujshed	2/1	12		Date/Tip	ne Received by: (Signature)  O D. Resluip
Relinquished by:  D. Redline	Date	/ Time /90 /83		eived b						quished				Date/Tin	ne Received by: (Signature)
Method of Shipment:		Shipped		pped by						er (Sig	_,			Received	d for tab. by: Date/Time
Distribution: Original Accompa	nies Sh	ipment;	Copy t	o Field	File	s						<del></del>			

A, INC. 10950 S.W. 5TH STREET SUITE 310 BEAVERTON, OREGON 97005

Phone (503)643-4661

Tax (503)643-4039		ينصصف												, حجسسته		
PROJECT PROJECT NAME			_					1	1					1 1	REMARKS	
316-00 TACOMA.	SLA (	5 51	(au)												i	
SAMPLERS/ (Signature)		<del></del> -		:												
Rich Harving				·							} .					
SAMPLE IDENTIFICATION	DATE	TIME	ORAB WPC	-GOMP												
Refine Top Wise TS1127921	11/27	3045	1/												House 2 - Gig Harbor	
1	III)	20													.,	
	11127	2120	Blank													
		2115		,												
		2115	<del></del>	V				.								
	1127			·:/												
nty Capet Kic Surger TS1127927		_														
Kenn line both TS1127928	11/27	2130		Blank												
lown not line TS1127929				Blank					_	1						
(100m Mar 1.0 to 1.2 1.1 1.7 2.1	1107	≥13C)		Diary			$\neg \vdash$	_		<del>                                     </del>						
	$\uparrow$						十			1						~
	-						$\dashv$			<del> </del>	<del>                                     </del>			+		
		\		<b></b> -						-	<del> </del>	$\vdash$				
		<del>/</del>	<u> </u>		-					<del>                                     </del>	<del> </del>	$\vdash$				
		/			-		L 			1	L		9			
		\		<u> </u>	<u> </u>		10	TAL NO	OF CO	NIAIN	:KS	<u> </u>	7			
Relinguished by: full Hawner		/ Time		eived b	y: (S	ignatur 100		R	elinqui	ished	by:			Date/Tim	e Received by: (Signature)	
Relinquished by:	Date	/ Time	Xec	eived b	y: (S			R	elinqu	ished	by:			Date/Tim	e Received by: (Signature)	
Method of Shipment:	Date	Shipped	i: Shi	pped by	': (Si	gnature	<b>)</b>		ourier	(Sign	ature	<b>)</b>		Received	for Lab. by: Date/	Time

10950 S.W. 5TH STREET SUITE 310

BEAVERTON, OREGON 97005

Phone (503)643-4661 Fax (503)643-4039

Fax (503) 643-4039								·					<del></del>		<del></del>	<del></del>				
PROJECT PROJECT NAME		,	,													REM	IARKS	/5		
316-001 TACOMA SL	AG	STU	Y												1		P. 1	/		
SAMPLERS (Signature)			. //	1. 10	,.	1					.		·							
SAMPLERS (Signatura) Rich M. Hanny Dan K	edle	ر و	12.5	Week											•					
	DATE	TIME	GRAB	COMP																
Yad So:1#1 TS1127930 1	1/28	9:00		V												H	ouse 3 - T	acoma		
	11/28			V																
		9:15		1																
	1128			1/								·						<del></del>		
XdG1+5 TS1177-934	אבנוו			1														<del></del>		
Drivary Slay #1 TS 1127935 1	11/28	9:45	V																<u></u>	
ariceway 9 ag #2 TS 1127936	11/28	1000	/																	
Wash-corer TS1127937	11/28	1030		blank																
	11/28	1030		blank																
	11/28		<b>:/</b>										ĮI.	,						
Vinyl Floor Uipe TS1127940	11/28	1120	<b>V</b>																	
Entry way carpet 731127941	11/28	1130		V																
Freezer Top Wipe #/ TS1127942			V																	
Fimily Room Capet 73/127943	11/08	1230		1/															·	
l '			/					TOTAL	NO. C	F CON	TAINE	RS		15						
Freezer Top Wipe #2 TS 112 7944	11100	/ Time	1 800	nivad b	1	L			Pal	inqui	bod l	~			Date/Tir		Bacalyad by	Sicontura)		
Relinquished by: Kuk Hanna		7 1111112 70 /670		eived b					"	iiiqu):	sileu (	.y.			vale/ i ii	1A3	Received by: (	aignature)		
Relinquished by:		/ Time		Received by: (Signature)						inqui	shed t	y:			Date/Ti	ne	Received by: (	Signature)		
	ļ		-				<del></del>		<u> </u>										·	
Method of Shipment:	pment: Date Shipped Shipped								Cou	rier	(Sign	ature)	)		Receive	ceived for Lab. by: Date/Time				
Distribution: Original Accompa	nies Sh	ipment;	Copy t	o Field	File	s			<u> </u>			<del>-</del>		L				·	1	

A, INC.

10950 S.W. 5TH STREET SUITE 310

BEAVERTON, OREGON 97005 Phone (503)643-4661 Fax (503)643-4039

PROJECT PROJECT NAME																REM	<b>WARKS</b>		
316-001 TACOMA SL	A6 S	TUDY							}							1	カーカー		
SAMPLERY (Signature) Rich M. Hawry	anfe	00-	11	11.1	Ď											ŀ	P. 2/2		
	DATE	TIME		COMP	þ														
SAMPLE IDENTIFICATION			GKAB	<u> </u>									<del></del> ‡		<u> </u>	<u> </u>			
Trip Wife Blank TS1124945	11/28	1130		Hank				_								ТН	louse 3 - Tacoma		
Entry Cottle und TS1127946	11/28	1700	V												<u> </u>				
an. Rm. Bottle with TS 1127947	11/28	1300	V																
Surge Vac TS1127948 Surge Bottle Wash TS1127949	11128	1300	V																
Surpe Boitle Way 751127949	11/28	13/5	/																
\																			
				}															
															1				
\																			
			\																
															1	T			
							·	TOTAL	NO. C	F CON	TAINE	RS		5					
Relinquished by:  Fin formy	,	/ Time '9) <i>[6]</i>	D Fee	eived b	y: (s	ignati	ure)		Rel	inqui	shed	by:			Date/Tim		ne Received by: (Signature)		
Relinquished by:	Date	Date / Time Received b					ure)		Rel	inqui	shed	by:			Date/Time		Received by: (Signature)		
Method of Shipment:	: Date Shipped Shipped by					gnatu	re)		Cou	rier	(Sign	ature;	· · · · · · · · · · · · · · · · · · ·		Received for Lab. by: Dat				

-AEA, NC

10950 S.W. 5TH STREET SUITE 310

BEAVERTON, OREGON 97005

Phone (503)643-4661 Fax (503)643-4039

# CHAIN OF CUSTODY RECORD

ax (503)643-4039	, 				T	T	·		T	7					T	DEMONS
PROJECT PROJECT NAME		_,	•					1		- 1						REMARKS
316-001 ) acoma ?	<u> 5 la c</u>	Sto	idy				,									
SAMPLERS (Signature)	ر م	,	0	:												
					-					- 1						
SAMPLE IDENTIFICATION	DATE	TIME	GRAB	COMP	<u> </u>										<u> </u>	Address EYA#
	12/14	9:30	/											ļ		House 2 - 48115
20 2/2 TS/127951	12/14	10:05	1													Gig Harbor 48116
inse 75/127952	12/14	10:22	17.	antr 15e												48114
218 3/1 T51127953	12/14	1):23	~													House 3- 48117
165 3/2 TS 1127954	12/14	11:50	/													Tacoma 48113
TIP Blant Yorket RinseTS112795	12/14	41.27	Rins	, ,	1				_							TACOMEC TOTAL
TIP DISTE THE NICE IS HOT IS	10.111	11.56.7	73.5		<del> </del>				$\neg$						1	
		<del></del>	<b> </b> -						_						-	
		-			<del> </del>	-			_						-	
· ·					<del> </del>							·		 	-	
			<del> </del>	<del> </del>					+					-		
				·	<del> </del>	<del> </del>									-	
······································		<u> </u>			<del> </del>	<b> </b> -			-					ļ	_	
			<u> </u>		-				_					<u> </u>		
		<u> </u>			<u> </u>	<u> </u>	<u>.</u>							ļ		
							ī	OTAL N	0. OF	CON	TAINE	RS				
Relyinguished by:		/ Time	Rec	erived to	y; (s	ionati MWM	ure)		Relin	qui's	thed !	HAN	ma		Date/T	ine Received by: (Signature)
Relinquished by:		/ Time		eived b					Relin	nquis	hed	by:			Date/T	
Method of Shipment:	Date	Shipped	d Shi	pped by	/: (Si	gnatu		Cour	ier (	Sign	ature:	) <sub>.</sub>		Receive	red for Lab. by: Date/Time	
stribution: Original Accomp	anies St	inment.	Coov	o Field	File	•								!	<del></del>	

Distribution: Original Accompanies Shipment; Copy to field Files

10950 S.W. 5TH STREET SUITE 310

BEAVERTON, OREGON 97005 Phone (503)643-4661 Fax (503)643-4039

ax (503)643-403	<i>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</i>									<del></del>		7						
PROJECT PROJECT NAME  70  6-00 70  70  AMPLE IDENTIFICATION	S (	TIME	GRAB	СОМР	Car Sison	GFAA/1cP	4s, Pb			( \ ~	V	IO				RE	TACOMA SLAG STUDY QUALT ASSILANCE	; TY
	<u> </u>	<del>  </del>		<del> </del>	,	19		_	-	-				===	<del>- </del> -	+-	200	
51127956/CMI	12/17				0/	1			90	<u>s · </u>	149					5	Quality Hosevan	· Smo
51127956/CMI 51127957/CM2	12/2				/						150					1	Quality Assurance	Samo
	7													٠.				Ū
	<del>                                     </del>					<b></b> -									<del>                                     </del>	-	<del></del>	
	<del> </del>					-				<b> </b> -				<del></del>				<del></del>
	<del> </del>			ļ	<b> </b> -										<del></del>			
	<u> </u>				<u> </u>			<u> </u>								4		<del></del>
																_		
													- l					
	1														1	1		
	<del> </del>				<del> </del>			-	<u> </u>	<del> </del>						+-		<del></del>
	<del> </del>				╂													
	<del> </del>				ļ			<u> </u>			<u> </u>							<del></del>
		<u> </u>			<u>                                     </u>	<u> </u>												
														1				
	-				1											1	· · · · · · · · · · · · · · · · · · ·	
	<del> </del>			<del> </del>	-		L	L	L		L	لــــــا ا						<del></del>
	{	1					1	TOTAL	NO. C	OF CON	ITAINE	RS						
telinquished by:	Date	/ Time	Rec	eived b	y: (S	ignatı	ure)		Rel	inqui	shed l	oy:			Date/Time		Received by: (Signature)	
elinquished by:	Date	/ Time	Rec	eived b	y: (S	ignati	ure)		Rel	inqui	shed	by:			Date/Time		Received by: (Signature)	
lethod of Shipment:	Date	Shipped	Shi	pped by	/: (Si	gnatu	re)	<u> </u>	Cou	Courier (Signature)						ed for	r Lab. by:	Date/Time
stribution: Original Accom	penies St	ipment:	Copy t	o Field	File	<u> </u>			ــــــــــــــــــــــــــــــــــــــ								<del></del>	

10% S.W. 5TH STREET SUITE 310 BEAVERTON, OREGON 97005 Phone (503)643-4661 Fax (503)643-4039

rax (503) 643-403	<i></i>																
PROJECT NAME NO 316-401 Tacoma SAMPLERS (Signature)	5100	St	J		1/6×14											REMARKS	is .
SAMPLE IDENTIFICATION	DATE	TIME	CRAS	COMP	\( \)								¥				
TS1127958/STD3	12/21/20		/		7											There are two standards for accuracy checks	se are two standards to
151127959/509	2/21/90			ļ	/		_									accuracy checks	uracly checo-
	<u> </u>			ļ	<u> -</u>									<u>'</u>			$\mathcal{O}$
							ļ							ļ	ļ		
														ļ			· · · · · · · · · · · · · · · · · · ·
	<u> </u>	<u> </u>	 			 	ļ						·	<u></u>	ļ		
							_	<u> </u>									<del></del>
	ļ	ļ		<u> </u>					<u> </u>	ļ				<u> </u>			
	ļ		ļ	<b> </b>					<b> </b>					ļ			
				<u> </u>	ļ						<u> </u>						
	<u> </u>									ļ	<u> </u>			ļ		·	
	<u> </u>		ļ			<u> </u>				<u> </u>				<b> </b>			
	ļ	ļ	<u> </u>		ļ		ļ	<u> </u>									
				ļ. 	ļ <u>.                                    </u>		<u> </u>	<u>.                                    </u>	i		<u> </u>	<u> </u>	Ĺ	ļ	<u> </u>		
								TOTAL	NO. (	OF COA	ITAINE	RS					·
Relinquished by:	Date	/ Time	Rec	eived b	y: (S	ignati	ure)		Rel	inqui	shed	by:			Date/Tir	ne Received by: (Signature)	eceived by: (Signature)
Relinquished by:	Date	/ Time	Rec	eived b	y: (S	ignati	ure)		Rel	inqui	shed	by:			Date/Tir	ne Received by: (Signature)	eceived by: (Signature)
Method of Shipment:		Shipped	·	pped by			re)		Cou	rier	(Sign	ature	)		Received	d for Lab. by: Date/T	b. by: Date/Ti
Distribution: Original Accom	panies Sh	i oment	Coov t	o Field	File	•											<del></del>